

The acepack Package

February 16, 2008

Maintainer Thomas Lumley <tlumley@u.washington.edu>

Version 1.3-2.2

Author Phil Spector, Jerome Friedman, Robert Tibshirani, Thomas Lumley

Description ACE and AVAS methods for choosing regression transformations.

Title ace() and avas() for selecting regression transformations

License avas is public domain, ace is on Statlib

R topics documented:

ace	1
avas	3
Index	5

ace *Alternating Conditional Expectations*

Description

Uses the alternating conditional expectations algorithm to find the transformations of y and x that maximise the proportion of variation in y explained by x.

Usage

```
ace(x, y, wt, cat, mon, lin, circ, delrsq)
```

Arguments

<code>x</code>	a matrix containing the independent variables.
<code>y</code>	a vector containing the response variable.
<code>wt</code>	an optional vector of weights.
<code>cat</code>	an optional integer vector specifying which variables assume categorical values. Positive values in <code>cat</code> refer to columns of the <code>x</code> matrix and zero to the response variable.
<code>mon</code>	an optional integer vector specifying which variables are to be transformed by monotone transformations. Positive values in <code>mon</code> refer to columns of the <code>x</code> matrix and zero to the response variable.
<code>lin</code>	an optional integer vector specifying which variables are to be transformed by linear transformations. Positive values in <code>lin</code> refer to columns of the <code>x</code> matrix and zero to the response variable.
<code>circ</code>	an integer vector specifying which variables assume circular (periodic) values. Positive values in <code>circ</code> refer to columns of the <code>x</code> matrix and zero to the response variable.
<code>delrsq</code>	termination threshold. Iteration stops when R-squared changes by less than <code>delrsq</code> in 3 consecutive iterations (default 0.01).

Value

A structure with the following components:

<code>x</code>	the input <code>x</code> matrix.
<code>y</code>	the input <code>y</code> vector.
<code>tx</code>	the transformed <code>x</code> values.
<code>ty</code>	the transformed <code>y</code> values.
<code>rsq</code>	the multiple R-squared value for the transformed values.
<code>l</code>	not used in this version of <code>ace</code>
<code>m</code>	not used in this version of <code>ace</code>

References

Breiman and Friedman, Journal of the American Statistical Association (September, 1985).

The R code is adapted from S code for `avas()` by Tibshirani, in the Statlib S archive; the FORTRAN is a double-precision version of FORTRAN code by Friedman and Spector in the Statlib general archive.

Examples

```
TWOPI <- 8*atan(1)
x <- runif(200,0,TWOPI)
y <- exp(sin(x)+rnorm(200)/2)
a <- ace(x,y)
par(mfrow=c(3,1))
```

```

plot(a$y,a$ty) # view the response transformation
plot(a$x,a$tx) # view the carrier transformation
plot(a$tx,a$ty) # examine the linearity of the fitted model

```

avas

Additivity and variance stabilization for regression

Description

Estimate transformations of x and y such that the regression of y on x is approximately linear with constant variance

Usage

```
avas(x, y, wt, cat, mon, lin, circ, delrsq, yspan)
```

Arguments

<code>x</code>	a matrix containing the independent variables.
<code>y</code>	a vector containing the response variable.
<code>wt</code>	an optional vector of weights.
<code>cat</code>	an optional integer vector specifying which variables assume categorical values. Positive values in <code>cat</code> refer to columns of the <code>x</code> matrix and zero to the response variable.
<code>mon</code>	an optional integer vector specifying which variables are to be transformed by monotone transformations. Positive values in <code>mon</code> refer to columns of the <code>x</code> matrix and zero to the response variable.
<code>lin</code>	an optional integer vector specifying which variables are to be transformed by linear transformations. Positive values in <code>lin</code> refer to columns of the <code>x</code> matrix and zero to the response variable.
<code>circ</code>	an integer vector specifying which variables assume circular (periodic) values. Positive values in <code>circ</code> refer to columns of the <code>x</code> matrix and zero to the response variable.
<code>delrsq</code>	termination threshold. Iteration stops when R-squared changes by less than <code>delrsq</code> in 3 consecutive iterations (default 0.01).
<code>yspan</code>	Optional window size parameter for smoothing the variance. Range is $[0, 1]$. Default is 0 (cross validated choice). <code>.5</code> is a reasonable alternative to try.

Value

A structure with the following components:

<code>x</code>	the input <code>x</code> matrix.
<code>y</code>	the input <code>y</code> vector.
<code>tx</code>	the transformed <code>x</code> values.

ty	the transformed y values.
rsq	the multiple R-squared value for the transformed values.
l	not used in this version of avas
m	not used in this version of avas
yspan	span used for smoothing the variance
iters	iteration number and rsq for that iteration
niters	number of iterations used

References

Rob Tibshirani (1987), “Estimating optimal transformations for regression”. *Journal of the American Statistical Association* **83**, 394ff.

Examples

```
TWOPI <- 8*atan(1)
x <- runif(200, 0, TWOPI)
y <- exp(sin(x)+rnorm(200)/2)
a <- avas(x,y)
par(mfrow=c(3,1))
plot(a$y,a$ty) # view the response transformation
plot(a$x,a$tx) # view the carrier transformation
plot(a$tx,a$ty) # examine the linearity of the fitted model
```

Index

*Topic **models**

ace, [1](#)
avas, [3](#)

ace, [1](#)
avas, [3](#)