

Package ‘distrTEst’

November 3, 2009

Version 2.2

Date 2009-10-16

Title Estimation and Testing classes based on package distr

Depends R(>= 2.6.0), methods, graphics, setRNG(>= 2006.2-1), distr(>= 2.2), distrSim(>= 2.2),
startupmsg

Suggests distrEx(>= 2.2)

Imports stats

Author Florian Camphausen, Matthias Kohl, Peter Ruckdeschel, Thomas Stabla

Description Evaluation (S4-)classes based on package distr for evaluating procedures
(estimators/tests) at data/simulation in a unified way.

Maintainer Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>

LazyLoad yes

Encoding latin1

License LGPL-3

URL <http://distr.r-forge.r-project.org/>

LastChangedDate {`$LastChangedDate: 2009-10-16 06:05:45 +0200 (Fr, 16. Okt 2009) $`}

LastChangedRevision {`$LastChangedRevision: 618 $`}

Repository CRAN

Date/Publication 2009-11-03 13:50:23

R topics documented:

distrTEst-package	2
call.ev-methods	4
Data-methods	4
distrTEstoptions	5
estimator-methods	6
evaluate-methods	6
Evaluation-class	7
EvaluationList-class	9
filename-methods	11
name-methods	11
numericorNULL-class	12
plot-methods	12
print-methods	13
result-methods	14
savedata-methods	14
summary-methods	15
Index	16

distrTEst-package *dsitrTEst – Estimation and Testing classes based on package distr*

Description

distrTest provides (S4-)classes for evaluating procedures (estimators/tests) at data/simulation in a unified way based on package **distr**. This is achieved by means of the S4 class `Evaluation`. The package is based on our packages **distr** and **distrSim**, hence uses distribution classes and simulation classes as introduced there to capture the situation from which the simulations stem.

Details

```

Package:   distrTEst
Version:   2.2
Date:      2009-09-04
Depends:   R(>= 2.6.0), methods, graphics, setRNG(>= 2006.2-1), distr(>= 2.0), distrSim(>= 2.0), startupmsg
LazyLoad:  yes
License:   LGPL-3
URL:       http://distr.r-forge.r-project.org/

```

Classes

```

"Evaluation"
  slots: [ <name> (<class> ) ]

```

```

      name(character), filename(character), call.ev(call),
      Data(Dataclass), result(DataframeorNULL),
      estimator(OptionalFunction)
"EvaluationList"
  slots: [<name>(<class>)]
  name(character), Elist(list)

```

Objects of class "Evaluation" are generated by a call to [evaluate](#).

Methods

plot	plot method for "Evaluation" and for "EvaluationList"
print, show	print/show method for "Evaluation" and for "EvaluationList"
summary	summary method for "Evaluation" and for "EvaluationList"
Data	accessor method for "Evaluation", and, for "EvaluationList" returns common Data

Slot accessors / -replacement functions

All slots are inspected / modified by corresponding accessors / -replacement functions, e.g. `call.ev(X)` or `filename(X) <- "myevaluation.sav"` for an object of class "Evaluation".

Start-up-Banner

You may suppress the start-up banner/message completely by setting options ("StartupBanner"="off") somewhere before loading this package by `library` or `require` in your R-code / R-session.

If option "StartupBanner" is not defined (default) or setting options ("StartupBanner"=NULL) or options ("StartupBanner"="complete") the complete start-up banner is displayed.

For any other value of option "StartupBanner" (i.e., not in `c(NULL, "off", "complete")`) only the version information is displayed.

The same can be achieved by wrapping the `library` or `require` call into either `suppressStartupMessages()` or `onlytypeStartupMessages(., atypes="version")`.

As for general packageStartupMessage's, you may also suppress all the start-up banner by wrapping the `library` or `require` call into `suppressPackageStartupMessages()` from `startupmsg`-version 0.5 on.

Package versions

Note: The first two numbers of package versions do not necessarily reflect package-individual development, but rather are chosen for the `distrXXX` family as a whole in order to ease updating "depends" information.

Note

Global options controlling the plots and summaries of Evaluationlist objects may be inspected / set by `distrTEstoptions()` and `getdistrTEstOption()`.

Author(s)

Thomas Stabla <statho3@web.de>,
 Florian Camphausen <fcampi@gmx.de>,
 Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>,
 Matthias Kohl <Matthias.Kohl@stamats.de>

Maintainer: Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>

References

A vignette for packages **distr**, **distrSim**, **distrTEst**, and **distrEx** is included into the mere documentation package **distrDoc** and may be called by `require("distrDoc"); vignette("distr")`.

A homepage to this package is available under
<http://distr.r-forge.r-project.org/>

See Also

[distr-package](#), [distrSim-package](#), [setRNG](#)

`call.ev-methods` *Methods for Function `call.ev` in Package ‘distrTEst’*

Description

`call.ev-methods`

Methods

call.ev `signature(object = "Evaluation")`: returns the call which created the object

`Data-methods` *Methods for Function `Data` in Package ‘distrTEst’*

Description

`Data-methods`

Methods

Data `signature(object = "Evaluation")`: returns the `Data` slot

Data `signature(object = "EvaluationList")`: returns the common `Data` slot of the respective list elements

distrTEoptions *functions to change the global variables of the package 'distrTEst'*

Description

With `distrTEoptions` and `getdistrTEstOption` you may inspect and change the global variables used by package **distrTEst**.

Usage

```
distrTEoptions(...)
getdistrTEstOption(x)
```

Arguments

`...` any options can be defined, using `name = value` or by passing a list of such tagged values.

`x` a character string holding an option name.

Details

Invoking `distrTEoptions()` with no arguments returns a list with the current values of the options. To access the value of a single option, one should use `getdistrTEstOption("MaxNumberOfSummarizedEvaluations")` e.g., rather than `distrTEoptions("MaxNumberOfSummarizedEvaluations")` which is a *list* of length one.

Value

`distrTEoptions()` returns a list of the global options of **distrTEst**.

`distrTEoptions("MaxNumberOfSummarizedEvaluations")` returns the global option `MaxNumberOfSummarizedEvaluations` as a list of length 1.

`distrTEoptions("MaxNumberOfSummarizedEvaluations" = 3)` sets the value of the global option `MaxNumberOfSummarizedEvaluations` to 3. `getdistrTEstOption("MaxNumberOfSummarizedEvaluations")` returns the current value set for option `MaxNumberOfSummarizedEvaluations`.

Currently available options

MaxNumberOfPlottedEvaluations maximal number of evaluations plotted; defaults to 6

MaxNumberOfPlottedEvaluationDims maximal number of evaluation dimensions plotted in parallel; defaults to 6

MaxNumberOfSummarizedEvaluations maximal number of evaluations summarized in parallel; defaults to 15

MaxNumberOfPrintedEvaluations maximal number of evaluations printed in parallel; defaults to 15

Author(s)

Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>

See Also

[options](#), [getOption](#), [distrOptions](#), [getDistrOption](#)

Examples

```
distrTEstoptions()
distrTEstoptions("MaxNumberOfPlottedEvaluationDims")
distrTEstoptions("MaxNumberOfPlottedEvaluationDims" = 5)
# or
getDistrTEstOption("MaxNumberOfPlottedEvaluationDims")
```

estimator-methods *Methods for Function estimator in Package 'distrTEst'*

Description

estimator-methods

Methods

estimator signature(object = "Evaluation"): returns the estimator

evaluate-methods *Methods for Function evaluate in Package 'distrTEst'*

Description

evaluate-methods to produce objects of class "Evaluation"

Arguments

object	the data set / simulation on which the evaluation takes place
estimator	the estimation function used; should be able to deal with data in matrix form <code>samplesize x obsDim</code> , and, should return either a univariate result or a vector (with named coordinates, if possible).
resname	(a vector of) character(s); the name for the univariate results or, in the case of multivariate results, and if the coordinates of the results have not yet been named, the basic name for them which is pasted to the coordinate number for each coordinate.
name	character; the name for the Evaluation object; by default the (R-)name of the Data set object.
filename	character; the filename for the Evaluation object (where it is to be saved to); by default the filename of the Data set object which is concatenated with the name of the estimator in <code>savedata</code> .

Details

besides the arguments determining the method dispatch, we have:

```
evaluate(object, estimator, ..., resname = "res",
         name = as.character(substitute(object)),
         filename = filename(object))
```

Methods

evaluate signature(object = "Dataclass", estimator = "function"): creates an object of class "Evaluation", see there for further information

evaluate signature(object = "Contsimulation", estimator = "function"): creates an object of class "Evaluation", see there for further information

See Also

[Evaluation-class](#)

Evaluation-class *Class "Evaluation"*

Description

When an estimator is used to data of the type "Dataclass" with the method evaluate, the result is an object of class "Evaluation".

Objects from the Class

Objects could be created by calls of the form `new("Evaluation", Data, estimator, [result, name, filename, call.ev])`. It does not seem to be very useful to generate a new object this way, however. It is to be preferred to use "evaluate" with a Dataclass object!

Slots

call.ev Object of class "call": the call which created the object, e.g.; "evaluate(Dataclassobject,mean)"

Data Object of class "Dataclass": the data set / simulation on which the evaluation takes place.

estimator Object of class "OptionalFunction": estimation function used; this estimation function should be able to deal with data in matrix form `samplesize x obsDim` and should return either a univariate result or a vector (with named coordinates, if possible).

filename Object of class "character": the filename of the evaluation; by default the filename of the Dataclass object, which was called by evaluate

name Object of class "character": the name of the evaluation; by default the name of the Dataclass object, which was called by evaluate

result Object of class "DataframeorNULL": the result of the evaluation of the estimation on data

Accessors/Replacement functions

call.ev no replacement possible
estimator no replacement possible
filename replacement possible
name replacement possible
result no replacement possible

Methods

initialize signature(.Object = "Evaluation"): initialize method
plot signature(object = "Evaluation"): returns a boxplot of the result
print signature(object = "Evaluation"): returns the name of the data object, its filename, the estimator used and the result
savedata signature(object = "Evaluation"): saves the object in two files in the directory of R - one with data, one without as comment file (see example)
summary signature(object = "Evaluation"): returns the name of the data object, its filename, the estimator used and a statistical summary of the result

Note

The saved "evaluation" can be loaded with the usual load-command, the saved comment with the function cload.

Author(s)

Thomas Stabla <statho3@web.de>,
 Florian Camphausen <fcampi@gmx.de>,
 Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>,
 Matthias Kohl <Matthias.Kohl@stamats.de>

See Also

[Dataclass-class Simulation-class Contsimulation-class load cload savedata-methods plot-methods simulate-methods summary-methods](#)

Examples

```
N <- Norm() # N is a standard normal distribution.
C <- Cauchy() # C is a Cauchy distribution
cs <- Contsimulation(filename = "csim",
                    runs = 5,
                    samplesize=5000,
                    seed=setRNG(),
                    distribution.id = N,
                    distribution.c = C,
                    rate = 0.1)

simulate(cs)
```

```

# Each of the 25000 random numbers is ideal (N-distributed) with
# probability 0.9 and contaminated (C-distributed) with probability = 0.1
summary(cs)
ev1 <- evaluate(cs, mean, resname="mean") # estimates the data with mean
ev1 # bad results
ev2 <- evaluate(cs, median, resname="median") # estimates the data with median
ev2 # better results because median is robust
savedata(ev1)
# saves the evaluation with result as "csim.mean" and without result as
# "csim.mean.comment" in the working directory # of R - "csim" is the
# filename of the Contsimulation object, mean the name of the estimator
rm(ev1)
cload("csim.mean")
# loads the evaluation without result - the object is called ev1.comment
ev1.comment
load("csim.mean") # loads the evaluation with result
ev1
plot(ev1)
#
#another function to be evaluated:
severalThings<- function(x) {list("mean"=mean(x), "sd"=sd(x), "mad"=mad(x))}
ev3 <- evaluate(cs, severalThings, resname="several")
plot(ev3)
plot(ev3, ylim=c(0,10), col=c("blue","green", "red"))

```

EvaluationList-class

Class "EvaluationList"

Description

Several objects of class "Evaluation" may be gathered in a list of class "EvaluationList", if they all have the same result-format and also share the same data-set.

Objects from the Class

Objects may be created by the generating function `EvaluationList`, i.e.; `EvaluationList(..., name0 = "a list of \"Evaluation\" objects")`, where all arguments passed through ... have to be objects of class "Evaluation", the corresponding result-slots have to contain data.frames of identical dimension; the corresponding calls have to have identical `object`-arguments (for the data set), and the corresponding `Data`-slots have to be identical.

Slots

name: Object of class "character": the name of the EvaluationList object

Elist: Object of class "list": the list of Evaluation objects

Accessor/Replacement methods

Elist signature(object = "EvaluationList"): returns the list with the Evaluation objects

name signature(object = "EvaluationList"): returns/modifies the name of the EvaluationList object

Methods

Data signature(object = "EvaluationList"): returns the common Data-slot of one of the Evaluation objects

plot signature(object = "EvaluationList"): returns grouped boxplots of the results

print signature(object = "EvaluationList"): for each list element returns the name of the data object, its filename, the estimator used and the result

show signature(object = "EvaluationList"): as print

summary signature(object = "EvaluationList"): returns the name of the data object, its filename, the estimator used and a statistical summary of the result

Author(s)

Thomas Stabla <statho3@web.de>,
 Florian Camphausen <fcampi@gmx.de>,
 Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>,
 Matthias Kohl <Matthias.Kohl@stamats.de>

See Also

[Dataclass-class](#) [Simulation-class](#) [Contsimulation-class](#) [Evaluation-class](#)
[print-methods](#) [plot-methods](#) [simulate-methods](#) [summary-methods](#)

Examples

```
N <- Norm() # N is a standard normal distribution.
C <- Cauchy() # C is a Cauchy distribution
cs <- Contsimulation(filename = "csim",
                    runs = 15,
                    samplesize=500,
                    seed=setRNG(),
                    distribution.id = N,
                    distribution.c = C,
                    rate = 0.1)

simulate(cs)
# Each of the 25000 random numbers is ideal (N-distributed) with
# probability 0.9 and contaminated (C-distributed) with probability = 0.1
summary(cs)
ev1 <- evaluate(cs, mean) # estimates the data with mean
ev1 # bad results
ev2 <- evaluate(cs,median) # estimates the data with median
ev2 # better results because median is robust
savedata(ev1)
```

```

# saves the EvaluationList with result as "csim.mean" and without result as
# "csim.mean.comment" in the working directory # of R - "csim" is the
# filename of the Contsimulation object, mean the name of the estimator
rm(ev1)
pload("csim.mean")
# loads the EvaluationList without result - the object is called ev1.comment
ev1.comment
load("csim.mean") # loads the EvaluationList with result
ev1
ElistObj <- EvaluationList(ev1, ev2, name0="myEvalList")
plot(ElistObj, ylim=matrix(c(-0.5, 0.5, 0.5, 4), nrow=2), main=c("location", "scale"))
plot(ElistObj, ylim=c(-0.5, 0.5), main=c("location"), runs0=3:12, dims0=1, evals0=2)
ElistObj
summary(ElistObj)

```

filename-methods *Methods for Function filename in Package 'distrTEST'*

Description

filename-methods

Methods

filename signature(object = "Evaluation"): returns the filename of the evaluated object

name-methods *Methods for Function name in Package 'distrTEST'*

Description

name-methods

Methods

name signature(object = "Evaluation"): returns the slot name of data object

name<- signature(.Object = "Evaluation"): modifies the slot name of data object

`numericorNULL-class`

Classes "numericorNULL", "CallorNULL", and "DataframeorNULL"

Description

auxiliary classes; may contain either a numeric vector or NULL [or a call / data.frame or NULL, respectively].

Objects from the Class

A virtual Class: No objects may be created from it.

Methods

No methods defined with class "numericorNULL", "CallorNULL", and "DataframeorNULL" in the signature.

Note

From version 1.8, the result slot of an object of class evaluation is of type "DataframeorNULL"

Author(s)

Thomas Stabla <statho3@web.de>,
Florian Camphausen <fcampi@gmx.de>,
Peter Ruckdeschel <Peter.Ruckdeschel@itwm.fraunhofer.de>,
Matthias Kohl <Matthias.Kohl@stamats.de>

See Also

[Evaluation-class](#)

plot-methods

Methods for Function plot in Package 'distrTEst'

Description

plot-methods

Methods

plot signature(x = "Evaluation", y="missing"): returns a boxplot of the result

plot signature(x = "EvaluationList", y="missing"): regroups the list according to the different columns/coordinates of the result of the evaluation; for each such coordinate a boxplot is generated containing possibly several procedures and if evaluated at a `Contsimulation` object also grouped into evaluations on ideal and real data. The `plot`-arguments `main` and `ylim` may be transmitted coordinatewise (i.e.; a vector of length (result-dimension), respectively a 2 x (result-dimension) matrix) or globally, using the usual recycling rules.

print-methods

Methods for Functions print and show in Package 'distrTEst'

Description

print/show-methods

Methods

print signature(x = "Evaluation"): returns the name of the data object, its filename, the estimator used and the result; optional arguments:

runs0 the indices of runs to be summarized;

dims0 the indices of result dimensions to be summarized;

internal argument:

inList decides if name of Dataobject and Datafile are printed out (which is done if `inLIST==FALSE`); defaults to `FALSE` but is `TRUE` when `summary` is called from `summary-method` for `signature(object = "EvaluationList")`

print signature(object = "EvaluationList"): after printing the name of the list, for each member of the list `print` is executed; optional arguments:

eval0 the indices of evaluations to be summarized;— of this vector `eval0` maximally `MaxNumberofSummarizedEvaluations` evaluations are summarized where `MaxNumberofPrintedEvaluations` is a global option, see [distrTEstoptions](#)

runs0 the indices of runs to be summarized;

dims0 the indices of observation dimensions to be summarized;

show signature(x = "Evaluation"): the same as `print` (without optional arguments)

show signature(x = "EvaluationList"): the same as `print` (without optional arguments)

result-methods *Methods for Function result in Package 'distrTEst'*

Description

result-methods

Methods

result signature(object = "Evaluation"): returns the result of an evaluation

savedata-methods *Methods for Function savedata in Package 'distrTEst'*

Description

savedata-methods

Methods

savedata signature(object = "Evaluation"): saves the object in two files in the directory of R - one with data —filename = <filename>—, one without as comment file —filename = <filename>.comment—(see example); <filename>the filename can be specified in the optional argument fileN; by default it is concatenated from the filename of the Dataclass object and the estimatorname, which you may either pass as argument estimatorName or it is taken as the R-name of the corresponding R-function.

Note

For an example, see [Simulation-class](#) and [Contsimulation-class](#)

See Also

[Dataclass-class](#) [Simulation-class](#) [Contsimulation-class](#) [Evaluation-class](#)

summary-methods *Methods for Function summary in Package 'distrTEst'*

Description

summary-methods

Methods

summary `signature(object = "Evaluation")`: returns the name of the data object, its filename, the estimator used and a statistical summary of the result; optional arguments:

runs0 the indices of runs to be summarized;

dims0 the indices of result dimensions to be summarized;

internal argument:

inList decides if name of Dataobject and Datafile are printed out (which is done if `inList==FALSE`); defaults to `FALSE` but is `TRUE` when `summary` is called from `summary-method` for `signature(object = "EvaluationList")`

summary `signature(object = "EvaluationList")`: returns, for each member of the list a summary of the corresponding Evaluation object; optional arguments:

eval0 the indices of evaluations to be summarized;— of this vector `eval0` maximally `MaxNumberOfSummarizedEvaluations` evaluations are summarized where `MaxNumberOfSummarizedEvaluations` is a global option, see [distrTEstoptions](#)

runs0 the indices of runs to be summarized;

dims0 the indices of observation dimensions to be summarized;

Index

- *Topic **classes**
 - numericorNULL-class, 11
- *Topic **file**
 - filename-methods, 11
 - savedata-methods, 14
- *Topic **hplot**
 - plot-methods, 12
- *Topic **list**
 - EvaluationList-class, 9
- *Topic **manip**
 - Evaluation-class, 7
 - EvaluationList-class, 9
- *Topic **methods**
 - call.ev-methods, 4
 - Data-methods, 4
 - estimator-methods, 6
 - evaluate-methods, 6
 - filename-methods, 11
 - name-methods, 11
 - plot-methods, 12
 - print-methods, 13
 - result-methods, 13
 - savedata-methods, 14
 - summary-methods, 14
- *Topic **misc**
 - distrTEstoptions, 4
- *Topic **package**
 - distrTEst-package, 2
- *Topic **print**
 - print-methods, 13
- call.ev (*call.ev-methods*), 4
- call.ev, Evaluation-method (*call.ev-methods*), 4
- call.ev-methods, 4
- CallorNULL-class (*numericorNULL-class*), 11
- cloud, 8
- Contsimulation-class, 8, 10, 14
- Data (*Data-methods*), 4
- Data, Evaluation-method (*Data-methods*), 4
- Data, EvaluationList-method (*Data-methods*), 4
- Data-methods, 4
- Dataclass-class, 8, 10, 14
- DataframeorNULL-class (*numericorNULL-class*), 11
- distr-package, 3
- distroptions, 5
- distrSim-package, 3
- distrTEst (*distrTEst-package*), 2
- distrTEst-package, 2
- distrTEstoptions, 3, 4, 13, 15
- Elist (*EvaluationList-class*), 9
- Elist, EvaluationList-method (*EvaluationList-class*), 9
- estimator (*estimator-methods*), 6
- estimator, Evaluation-method (*estimator-methods*), 6
- estimator-methods, 6
- evaluate, 2
- evaluate (*evaluate-methods*), 6
- evaluate, Contsimulation, function-method (*evaluate-methods*), 6
- evaluate, Dataclass, function-method (*evaluate-methods*), 6
- evaluate-methods, 6
- Evaluation-class, 7, 10, 12, 14
- Evaluation-class, 7
- EvaluationList (*EvaluationList-class*), 9
- EvaluationList-class, 9
- filename (*filename-methods*), 11
- filename, Evaluation-method (*filename-methods*), 11
- filename-methods, 11

getdistrOption, 5
 getdistrTEstOption, 3
 getdistrTEstOption
 (*distrTEstoptions*), 4
 getOption, 5

 initialize, Evaluation-method
 (*Evaluation-class*), 7
 initialize, EvaluationList-method
 (*EvaluationList-class*), 9

 load, 8

 MaxNumberOfPlottedEvaluationDims
 (*distrTEstoptions*), 4
 MaxNumberOfPlottedEvaluations
 (*distrTEstoptions*), 4
 MaxNumberOfSummarizedEvaluationDims
 (*distrTEstoptions*), 4
 MaxNumberOfSummarizedEvaluations
 (*distrTEstoptions*), 4

 name (*name-methods*), 11
 name, Evaluation-method
 (*name-methods*), 11
 name, EvaluationList-method
 (*EvaluationList-class*), 9
 name-methods, 11
 name<-, EvaluationList-method
 (*EvaluationList-class*), 9
 numericorNULL-class, 11

 onlytypeStartupMessages, 3
 options, 5

 plot, Evaluation, missing-method
 (*plot-methods*), 12
 plot, EvaluationList, missing-method
 (*plot-methods*), 12
 plot-methods, 8, 10
 plot-methods, 12
 print, Evaluation-method
 (*print-methods*), 13
 print, EvaluationList-method
 (*print-methods*), 13
 print-methods, 10
 print-methods, 13

 result (*result-methods*), 13

 result, Evaluation-method
 (*result-methods*), 13
 result-methods, 13

 savedata, 6
 savedata (*savedata-methods*), 14
 savedata, Evaluation-method
 (*savedata-methods*), 14
 savedata, EvaluationList-method
 (*EvaluationList-class*), 9
 savedata-methods, 8
 savedata-methods, 14
 setRNG, 3
 show, Evaluation-method
 (*print-methods*), 13
 show, EvaluationList-method
 (*print-methods*), 13
 show-methods (*print-methods*), 13
 simulate-methods, 8, 10
 Simulation-class, 8, 10, 14
 summary, Evaluation-method
 (*summary-methods*), 14
 summary, EvaluationList-method
 (*summary-methods*), 14
 summary-methods, 8, 10
 summary-methods, 14
 suppressStartupMessages, 3