

Package 'pls'

January 2, 2012

Version 2.3-0

Date 2011-11-27

Title Partial Least Squares and Principal Component regression

Author Bjørn-Helge Mevik, Ron Wehrens and Kristian Hovde Liland

Maintainer Bjørn-Helge Mevik <pls@mevik.net>

Encoding latin1

LazyLoad yes

LazyData yes

ZipData yes

Description Multivariate regression methods
Partial Least Squares Regression (PLSR), Principal Component
Regression (PCR) and Canonical Powered Partial Least Squares (CPPLS)

License GPL-2

URL <http://mevik.net/work/software/pls.html>

Depends R (>= 2.10)

Suggests MASS

Repository CRAN

Date/Publication 2011-11-28 12:00:06

R topics documented:

biplot.mvr	2
coef.mvr	4
coefplot	6
cppls.fit	8
crossval	11
cvsegments	13
gasoline	14
jack.test	15
kernelpls.fit	17
mayonnaise	18
msc	19
mvr	20
mvrCv	23
mvrVal	25
oliveoil	28
oscorespls.fit	28
plot.mvr	30
pls.options	31
predict.mvr	33
predplot	34
scoreplot	36
scores	40
simpls.fit	41
stdize	43
summary.mvr	44
svdpc.fit	45
validationplot	46
var.jack	49
widekernelpls.fit	50
yarn	52
Index	54

biplot.mvr	<i>Biplots of PLSR and PCR Models.</i>
------------	--

Description

Biplot method for mvr objects.

Usage

```
## S3 method for class 'mvr'
biplot(x, comps = 1:2, which = c("x", "y", "scores", "loadings"),
       var.axes = FALSE, xlabs, ylabs, main, ...)
```

Arguments

x	an mvr object.
comps	integer vector of length two. The components to plot.
which	character. Which matrices to plot. One of "x" (X scores and loadings), "y" (Y scores and loadings), "scores" (X and Y scores) and "loadings" (X and Y loadings).
var.axes	logical. If TRUE, the second set of points have arrows representing them.
xlabs	either a character vector of labels for the first set of points, or FALSE for no labels. If missing, the row names of the first matrix is used as labels.
ylabs	either a character vector of labels for the second set of points, or FALSE for no labels. If missing, the row names of the second matrix is used as labels.
main	character. Title of plot. If missing, a title is constructed by biplot.mvr.
...	Further arguments passed on to biplot.default.

Details

biplot.mvr can also be called through the mvr plot method by specifying `plottype = "biplot"`.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [plot.mvr](#), [biplot.default](#)

Examples

```
data(oliveoil)
mod <- pls(sensory ~ chemical, data = oliveoil)
## Not run:
## These are equivalent
biplot(mod)
plot(mod, plottype = "biplot")

## The four combinations of x and y points:
par(mfrow = c(2,2))
biplot(mod, which = "x") # Default
biplot(mod, which = "y")
biplot(mod, which = "scores")
biplot(mod, which = "loadings")

## End(Not run)
```

coef.mvr

*Extract Information From a Fitted PLSR or PCR Model***Description**

Functions to extract information from `mvr` objects: Regression coefficients, fitted values, residuals, the model frame, the model matrix, names of the variables and components, and the X variance explained by the components.

Usage

```
## S3 method for class 'mvr'
coef(object, ncomp = object$ncomp, comps, intercept = FALSE, ...)
## S3 method for class 'mvr'
fitted(object, ...)
## S3 method for class 'mvr'
residuals(object, ...)
## S3 method for class 'mvr'
model.matrix(object, ...)
## S3 method for class 'mvr'
model.frame(formula, ...)
prednames(object, intercept = FALSE)
respnames(object)
compnames(object, comps, explvar = FALSE, ...)
explvar(object)
```

Arguments

<code>object, formula</code>	an <code>mvr</code> object. The fitted model.
<code>ncomp, comps</code>	vector of positive integers. The components to include in the coefficients or to extract the names of. See below.
<code>intercept</code>	logical. Whether coefficients for the intercept should be included. Ignored if <code>comps</code> is specified. Defaults to <code>FALSE</code> .
<code>explvar</code>	logical. Whether the explained X variance should be appended to the component names.
<code>...</code>	other arguments sent to underlying functions. Currently only used for <code>model.frame.mvr</code> and <code>model.matrix.mvr</code> .

Details

These functions are mostly used inside other functions. (Functions `coef.mvr`, `fitted.mvr` and `residuals.mvr` are usually called through their generic functions `coef`, `fitted` and `residuals`, respectively.)

coef.mvr is used to extract the regression coefficients of a model, i.e. the B in $y = XB$ (for the Q in $y = TQ$ where T is the scores, see [Yloadings](#)). An array of dimension $c(nxvar, nyvar, length(ncomp))$ or $c(nxvar, nyvar, length(comps))$ is returned.

If comps is missing (or is NULL), coef()[, , ncomp[i]] are the coefficients for models with ncomp[i] components, for $i = 1, \dots, length(ncomp)$. Also, if intercept = TRUE, the first dimension is $nxvar + 1$, with the intercept coefficients as the first row.

If comps is given, however, coef()[, , comps[i]] are the coefficients for a model with only the component comps[i], i.e. the contribution of the component comps[i] on the regression coefficients.

fitted.mvr and residuals.mvr return the fitted values and residuals, respectively. If the model was fitted with na.action = na.exclude (or after setting the default na.action to "na.exclude" with [options](#)), the fitted values (or residuals) corresponding to excluded observations are returned as NA; otherwise, they are omitted.

model.frame.mvr returns the model frame; i.e. a data frame with all variables necessary to generate the model matrix. See [model.frame](#) for details.

model.matrix.mvr returns the (possibly coded) matrix used as X in the fitting. See [model.matrix](#) for details.

prednames, respnames and compnames extract the names of the X variables, responses and components, respectively. With intercept = TRUE in prednames, the name of the intercept variable (i.e. "(Intercept)") is returned as well. compnames can also extract component names from score and loading matrices. If explvar = TRUE in compnames, the explained variance for each component (if available) is appended to the component names. For optimal formatting of the explained variances when not all components are to be used, one should specify the desired components with the argument comps.

explvar extracts the amount of X variance (in per cent) explained by for each component in the model. It can also handle score and loading matrices returned by [scores](#) and [loadings](#).

Value

coef.mvr returns an array of regression coefficients.

fitted.mvr returns an array with fitted values.

residuals.mvr returns an array with residuals.

model.frame.mvr returns a data frame.

model.matrix.mvr returns the X matrix.

prednames, respnames and compnames return a character vector with the corresponding names.

explvar returns a numeric vector with the explained variances, or NULL if not available.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [coef](#), [fitted](#), [residuals](#), [model.frame](#), [model.matrix](#), [na.omit](#)

Examples

```
data(yarn)
mod <- pcr(density ~ NIR, data = yarn[yarn$train,], ncomp = 5)
B <- coef(mod, ncomp = 3, intercept = TRUE)
## A manual predict method:
stopifnot(drop(B[1,,] + yarn$NIR[!yarn$train,] %*% B[-1,,]) ==
           drop(predict(mod, ncomp = 3, newdata = yarn[!yarn$train,])))

## Note the difference in formatting:
mod2 <- pcr(density ~ NIR, data = yarn[yarn$train,])
compnames(mod2, explvar = TRUE)[1:3]
compnames(mod2, comps = 1:3, explvar = TRUE)
```

coefplot

Plot Regression Coefficients of PLSR and PCR models

Description

Function to plot the regression coefficients of an mvr object.

Usage

```
coefplot(object, ncomp = object$ncomp, comps, intercept = FALSE,
         separate = FALSE, se.whiskers = FALSE, nCols, nRows, labels,
         type = "l", lty, lwd = NULL, pch, cex = NULL, col, legendpos,
         xlab = "variable", ylab = "regression coefficient", main,
         pretty.xlabels = TRUE, xlim, ylim, ...)
```

Arguments

object	an mvr object. The fitted model.
ncomp, comps	vector of positive integers. The components to plot. See coef.mvr for details.
separate	logical. If TRUE, coefficients for different model sizes are blotted in separate plots.
se.whiskers	logical. If TRUE, whiskers at plus/minus 1 estimated standard error are added to the plot. This is only available if the model was cross-validated with jackknife = TRUE. Also, in the current implementation, intercept must be FALSE, and separate must be TRUE if length(ncomp) > 1.
intercept	logical. Whether coefficients for the intercept should be plotted. Ignored if comps is specified. Defaults to FALSE. See coef.mvr for details.
nCols, nRows	integer. The number of columns and rows the plots will be laid out in. If not specified, coefplot tries to be intelligent.
labels	optional. Alternative <i>x</i> axis labels. See Details.
type	character. What type of plot to make. Defaults to "l" (lines). Alternative types include "p" (points) and "b" (both). See plot for a complete list of types.

<code>lty</code>	vector of line types (recycled as necessary). Line types can be specified as integers or character strings (see par for the details).
<code>lwd</code>	vector of positive numbers (recycled as necessary), giving the width of the lines.
<code>pch</code>	plot character. A character string or a vector of single characters or integers (recycled as necessary). See points for all alternatives.
<code>cex</code>	numeric vector of character expansion sizes (recycled as necessary) for the plotted symbols.
<code>col</code>	character or integer vector of colors for plotted lines and symbols (recycled as necessary). See par for the details.
<code>legendpos</code>	Legend position. Optional. Ignored if <code>separate</code> is TRUE. If present, a legend is drawn at the given position. The position can be specified symbolically (e.g., <code>legendpos = "topright"</code>). This requires R \geq 2.1.0. Alternatively, the position can be specified explicitly (<code>legendpos = t(c(x,y))</code>) or interactively (<code>legendpos = locator()</code>). This only works well for plots of single-response models.
<code>xlab,ylab</code>	titles for x and y axes. Typically character strings, but can be expressions (e.g., <code>expression(R^2)</code>) or lists. See title for details.
<code>main</code>	optional main title for the plot. See Details.
<code>pretty.xlabels</code>	logical. If TRUE, <code>coefplot</code> tries to plot the x labels more nicely. See Details.
<code>xlim,ylim</code>	optional vector of length two, with the x or y limits of the plot.
<code>...</code>	Further arguments sent to the underlying plot functions.

Details

`coefplot` handles multiple responses by making one plot for each response. If `separate` is TRUE, separate plots are made for each combination of model size and response. The plots are laid out in a rectangular fashion.

If `legendpos` is given, a legend is drawn at the given position (unless `separate` is TRUE).

The argument `labels` can be a vector of labels or one of "names" and "numbers". The labels are used as x axis labels. If `labels` is "names" or "numbers", the variable names are used as labels, the difference being that with "numbers", the variable names are converted to numbers, if possible. Variable names of the forms "number" or "number text" (where the space is optional), are handled.

The argument `main` can be used to specify the main title of the plot. It is handled in a non-standard way. If there is only one (sub) plot, `main` will be used as the main title of the plot. If there is *more* than one (sub) plot, however, the presence of `main` will produce a corresponding 'global' title on the page. Any graphical parameters, e.g., `cex.main`, supplied to `coefplot` will only affect the 'ordinary' plot titles, not the 'global' one. Its appearance can be changed by setting the parameters with [par](#), which will affect *both* titles. (To have different settings for the two titles, one can override the `par` settings with arguments to `coefplot`.)

The argument `pretty.xlabels` is only used when `labels` is specified. If TRUE (default), the code tries to use a 'pretty' selection of labels. If `labels` is "numbers", it also uses the numerical values of the labels for horizontal spacing. If one has excluded parts of the spectral region, one might therefore want to use `pretty.xlabels = FALSE`.

When `separate` is `TRUE`, the arguments `lty`, `col`, and `pch` default to their `par()` setting. Otherwise, the default for all of them is `1:nLines`, where `nLines` is the number of model sizes specified, i.e., the length of `ncomp` or `comps`.

The function can also be called through the `mvr` plot method by specifying `plottype = "coefficients"`.

Note

[legend](#) has many options. If you want greater control over the appearance of the legend, omit the `legendpos` argument and call `legend` manually.

The handling of labels and `pretty.xlabels` is experimental.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [plot.mvr](#), [coef.mvr](#), [plot](#), [legend](#)

Examples

```
data(yarn)
mod.nir <- plsr(density ~ NIR, ncomp = 8, data = yarn)
## Not run:
coefplot(mod.nir, ncomp = 1:6)
plot(mod.nir, plottype = "coefficients", ncomp = 1:6) # Equivalent to the previous
## Plot with legend:
coefplot(mod.nir, ncom = 1:6, legendpos = "bottomright")

## End(Not run)

data(oliveoil)
mod.sens <- plsr(sensory ~ chemical, ncomp = 4, data = oliveoil)
## Not run: coefplot(mod.sens, ncomp = 2:4, separate = TRUE)
```

cppls.fit

CPPLS (Indahl et al.)

Description

Fits a PLS model using the CPPLS algorithm.

Usage

```
cppls.fit(X, Y, ncomp, Y.add = NULL, stripped = FALSE, lower = 0.5, upper = 0.5, trunc.pow = FALSE, weigh
```

Arguments

X	a matrix of observations. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
Y.add	a vector or matrix of additional responses containing relevant information about the observations.
stripped	logical. If TRUE the calculations are stripped as much as possible for speed; this is meant for use with cross-validation or simulations when only the coefficients are needed. Defaults to FALSE.
lower	a vector of lower limits for power optimisation. Defaults to 0.5.
upper	a vector of upper limits for power optimisation. Defaults to 0.5.
trunc.pow	logical. If TRUE an experimental alternative power algorithm is used. (Optional)
weights	a vector of individual weights for the observations. (Optional)
...	other arguments. Currently ignored.

Details

This function should not be called directly, but through the generic functions `cppls` or `mvr` with the argument `method="cppls"`. Canonical Powered PLS (CPPLS) is a generalisation of PLS incorporating discrete and continuous responses (also simultaneously), additional responses, individual weighting of observations and power methodology for sharpening focus on groups of variables. Depending on the input to `cppls` it can produce the following special cases:

- PLS: uni-response continuous Y
- PPLS: uni-response continuous Y, (`lower` || `upper`) != 0.5
- PLS-DA (using correlation maximisation - B/W): dummy-coded discrete response Y
- PPLS-DA: dummy-coded discrete response Y, (`lower` || `upper`) != 0.5
- CPLS: multi-response Y (continuous, discrete or combination)
- CPPLS: multi-response Y (continuous, discrete or combination), (`lower` || `upper`) != 0.5

The name "canonical" comes from canonical correlation analysis which is used when calculating vectors of loading weights, while "powered" refers to a reparameterisation of the vectors of loading weights which can be optimised over a given interval.

Value

A list containing the following components is returned:

coefficients	an array of regression coefficients for 1, ..., ncomp components. The dimensions of coefficients are $c(nvar, npred, ncomp)$ with <code>nvar</code> the number of X variables and <code>npred</code> the number of variables to be predicted in Y.
scores	a matrix of scores.
loadings	a matrix of loadings.
loading.weights	a matrix of loading weights.

Yscores	a matrix of Y-scores.
Yloadings	a matrix of Y-loadings.
projection	the projection matrix used to convert X to scores.
Xmeans	a vector of means of the X variables.
Ymeans	a vector of means of the Y variables.
fitted.values	an array of fitted values. The dimensions of fitted.values are c(nobj, npred, ncomp) with nobj the number samples and npred the number of Y variables.
residuals	an array of regression residuals. It has the same dimensions as fitted.values.
Xvar	a vector with the amount of X-variance explained by each number of components.
Xtotvar	total variance in X.
gammas	gamma-values obtained in power optimisation.
canonical.correlations	Canonical correlation values from the calculations of loading weights.
A	matrix containing vectors of weights a from canonical correlation (cor(Za, Yb)).
smallNorms	vector of indices of explanatory variables of length close to or equal to 0.

If stripped is TRUE, only the components coefficients, Xmeans, Ymeans and gammas are returned.

Author(s)

Kristian Hovde Liland

References

- Indahl, U. (2005) A twist to partial least squares regression. *Journal of Chemometrics*, **19**, 32–44.
- Liland, K.H and Indahl, U.G (2009) Powered partial least squares discriminant analysis, *Journal of Chemometrics*, **23**, 7–18.
- Indahl, U.G., Liland, K.H. and Næs, T. (2009) Canonical partial least squares - a unified PLS approach to classification and regression problems. *Journal of Chemometrics*, **23**, 495–504.

See Also

[mvr](#) [pls](#) [pcr](#) [widekernelpls.fit](#) [simpls.fit](#) [oscorespls.fit](#)

Examples

```
data(mayonnaise)
# Create dummy response
mayonnaise$dummy <- I(model.matrix(~y-1, data.frame(y=factor(mayonnaise$oil.type))))

# Predict CPLS scores for test data
may.cpls <- cppls(dummy ~ NIR, 10, data = mayonnaise, subset = train)
may.test <- predict(may.cpls, newdata = mayonnaise[!mayonnaise$train,], type = "score")
```

```

# Predict CPLs scores for test data (experimental used design as additional Y information)
may.cpls.yadd <- cppls(dummy ~ NIR, 10, data = mayonnaise, subset = train, Y.add=design)
may.test.yadd <- predict(may.cpls.yadd, newdata = mayonnaise[!mayonnaise$train,], type = "score")

# Classification by linear discriminant analysis (LDA)
library(MASS)
error <- matrix(ncol = 10,nrow = 2)
dimnames(error) <- list(Model=c('CPLS','CPLS (Y.add)'), ncomp=1:10)
for(i in 1:10){
  error[1,i] <- ( 42 - sum(predict(lda(oil.type ~ NIR.score,
    data = data.frame(oil.type = mayonnaise$oil.type[ mayonnaise$train ], NIR.score = I(may.cpls$scores[,1:i,drop=F
    newdata = data.frame(NIR.score = I(may.test[,1:i,drop=FALSE])))$class == mayonnaise$oil.type[!mayonnaise$train
  error[2,i] <- ( 42 - sum(predict(lda(oil.type ~ NIR.score,
    data = data.frame(oil.type = mayonnaise$oil.type[mayonnaise$train], NIR.score = I(may.cpls.yadd$scores[,1:i,dr
    newdata = data.frame(NIR.score = I(may.test.yadd[,1:i,drop=FALSE])))$class == mayonnaise$oil.type[!mayonnaise
  }
  round(error,2)

```

crossval

*Cross-validation of PLSR and PCR models***Description**

A “stand alone” cross-validation function for mvr objects.

Usage

```

crossval(object, segments = 10,
         segment.type = c("random", "consecutive", "interleaved"),
         length.seg, jackknife = FALSE, trace = 15, ...)

```

Arguments

object	an mvr object; the regression to cross-validate.
segments	the number of segments to use, or a list with segments (see below).
segment.type	the type of segments to use. Ignored if segments is a list.
length.seg	Positive integer. The length of the segments to use. If specified, it overrides segments unless segments is a list.
jackknife	logical. Whether jackknifing of regression coefficients should be performed.
trace	if TRUE, tracing is turned on. If numeric, it denotes a time limit (in seconds). If the estimated total time of the cross-validation exceeds this limit, tracing is turned on.
...	additional arguments, sent to the underlying fit function.

Details

This function performs cross-validation on a model fit by `mvr`. It can handle models such as `plsr(y ~ msc(X), ...)` or other models where the predictor variables need to be recalculated for each segment. When recalculation is not needed, the result of `crossval(mvr(...))` is identical to `mvr(..., validation = "CV")`, but slower.

Note that to use `crossval`, the data *must* be specified with a `data` argument when fitting object.

If `segments` is a list, the arguments `segment.type` and `length.seg` are ignored. The elements of the list should be integer vectors specifying the indices of the segments. See [cvsegments](#) for details.

Otherwise, segments of type `segment.type` are generated. How many segments to generate is selected by specifying the number of segments in `segments`, or giving the segment length in `length.seg`. If both are specified, `segments` is ignored.

If `jackknife` is `TRUE`, jackknifed regression coefficients are returned, which can be used for variance estimation ([var.jack](#)) or hypothesis testing ([jack.test](#)).

When tracing is turned on, the segment number is printed for each segment.

Value

The supplied object is returned, with an additional component `validation`, which is a list with components

<code>method</code>	equals "CV" for cross-validation.
<code>pred</code>	an array with the cross-validated predictions.
<code>coefficients</code>	(only if <code>jackknife</code> is <code>TRUE</code>) an array with the jackknifed regression coefficients. The dimensions correspond to the predictors, responses, number of components, and segments, respectively.
<code>PRESS0</code>	a vector of PRESS values (one for each response variable) for a model with zero components, i.e., only the intercept.
<code>PRESS</code>	a matrix of PRESS values for models with 1, ..., <code>ncomp</code> components. Each row corresponds to one response variable.
<code>adj</code>	a matrix of adjustment values for calculating bias corrected MSE. MSE uses this.
<code>segments</code>	the list of segments used in the cross-validation.
<code>ncomp</code>	the number of components.
<code>gammas</code>	if method <code>cpp1s</code> is used, gamma values for the powers of each CV segment are returned.

Note

The `PRESS0` is always cross-validated using leave-one-out cross-validation. This usually makes little difference in practice, but should be fixed for correctness.

The current implementation of the jackknife stores all jackknife-replicates of the regression coefficients, which can be very costly for large matrices. This might change in a future version.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

Mevik, B.-H., Cederkvist, H. R. (2004) Mean Squared Error of Prediction (MSEP) Estimates for Principal Component Regression (PCR) and Partial Least Squares Regression (PLSR). *Journal of Chemometrics*, **18**(9), 422–429.

See Also

[mvr](#) [mvrCv](#) [cvsegments](#) [MSEP](#) [var.jack](#) [jack.test](#)

Examples

```
data(yarn)
yarn.pcr <- pcr(density ~ msc(NIR), 6, data = yarn)
yarn.cv <- crossval(yarn.pcr, segments = 10)
## Not run: plot(MSEP(yarn.cv))
```

cvsegments

Generate segments for cross-validation

Description

The function generates a list of segments for cross-validation. Random, consecutive and interleaved segments can be produced.

Usage

```
cvsegments(N, k, length.seg = ceiling(N/k),
           type = c("random", "consecutive", "interleaved"))
```

Arguments

N	Integer. The number of objects in the data set.
k	Integer. The number of segments to return.
length.seg	Integer. The length of the segments. If given, it overrides k.
type	One of "random", "consecutive" and "interleaved". The type of segments to generate. Default is "random".

Details

If `length.seg` is specified, it is used to calculate the number of segments to generate. Otherwise `k` must be specified. If $k * length.seg \neq N$, the $k * length.seg - N$ last segments will contain only $length.seg - 1$ indices.

If `type` is "random", the indices are allocated to segments in random order. If it is "consecutive", the first segment will contain the first $length.seg$ indices, and so on. If `type` is "interleaved", the first segment will contain the indices $1, length.seg + 1, 2 * length.seg + 1, \dots, (k - 1) * length.seg + 1$, and so on.

Value

A list of vectors. Each vector contains the indices for one segment. The attribute "incomplete" contains the number of incomplete segments, and the attribute "type" contains the type of segments.

Author(s)

Bjørn-Helge Mevik and Ron Wehrens

Examples

```
## Segments for 10-fold randomised cross-validation:
cvsegments(100, 10)

## Segments with four objects, taken consecutive:
cvsegments(60, length.seg = 4, type = "cons")

## Incomplete segments
segs <- cvsegments(50, length.seg = 3)
attr(segs, "incomplete")

## Leave-one-out cross-validation:
cvsegments(100, 100)
## Leave-one-out with variable/unknown data set size n:
n <- 50
cvsegments(n, length.seg = 1)
```

gasoline

Octane numbers and NIR spectra of gasoline

Description

A data set with NIR spectra and octane numbers of 60 gasoline samples. The NIR spectra were measured using diffuse reflectance as $\log(1/R)$ from 900 nm to 1700 nm in 2 nm intervals, giving 401 wavelengths. Many thanks to John H. Kalivas.

Usage

gasoline

Format

A data frame with 60 observations on the following 2 variables.

octane a numeric vector. The octane number.

NIR a matrix with 401 columns. The NIR spectrum.

Source

Kalivas, John H. (1997) Two Data Sets of Near Infrared Spectra *Chemometrics and Intelligent Laboratory Systems*, **37**, 255–259.

jack.test	<i>Jackknife approximate t tests of regression coefficients</i>
-----------	---

Description

Performs approximate t tests of regression coefficients based on jackknife variance estimates.

Usage

```
jack.test(object, ncomp = object$ncomp, use.mean = TRUE)
## S3 method for class 'jacktest'
print(x, P.values = TRUE, ...)
```

Arguments

object	an mvr object. A cross-validated model fitted with <code>jackknife = TRUE</code> .
ncomp	the number of components to use for estimating the variances
use.mean	logical. If TRUE (default), the mean coefficients are used when estimating the (co)variances; otherwise the coefficients from a model fitted to the entire data set. See var.jack for details.
x	an jacktest object, the result of <code>jack.test</code> .
P.values	logical. Whether to print p values (default).
...	Further arguments sent to the underlying print function printCoefmat .

Details

`jack.test` uses the variance estimates from `var.jack` to perform t tests of the regression coefficients. The resulting object has a print method, `print.jacktest`, which uses [printCoefmat](#) for the actual printing.

Value

jack.test returns an object of class "jacktest", with components

coefficients	The estimated regression coefficients
sd	The square root of the jackknife variance estimates
tvalues	The t statistics
df	The 'degrees of freedom' used for calculating p values
pvalues	The calculated p values

print.jacktest returns the "jacktest" object (invisibly).

Warning

The jackknife variance estimates are known to be biased (see [var.jack](#)). Also, the distribution of the regression coefficient estimates and the jackknife variance estimates are unknown (at least in PLSR/PCR). Consequently, the distribution (and in particular, the degrees of freedom) of the resulting t statistics is unknown. The present code simply assumes a t distribution with $m - 1$ degrees of freedom, where m is the number of cross-validation segments.

Therefore, the resulting p values should not be used uncritically, and should perhaps be regarded as mere indicator of (non-)significance.

Finally, also keep in mind that as the number of predictor variables increase, the problem of multiple tests increases correspondingly.

Author(s)

Bjørn-Helge Mevik

References

Martens H. and Martens M. (2000) Modified Jack-knife Estimation of Parameter Uncertainty in Bilinear Modelling by Partial Least Squares Regression (PLSR). *Food Quality and Preference*, **11**, 5–16.

See Also

[var.jack](#), [mvrCv](#)

Examples

```
data(oliveoil)
mod <- pcr(sensory ~ chemical, data = oliveoil, validation = "LOO", jackknife = TRUE)
jack.test(mod, ncomp = 2)
```

kernelpls.fit	<i>Kernel PLS (Dayal and MacGregor)</i>
---------------	---

Description

Fits a PLSR model with the kernel algorithm.

Usage

```
kernelpls.fit(X, Y, ncomp, stripped = FALSE, ...)
```

Arguments

X	a matrix of observations. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
stripped	logical. If TRUE the calculations are stripped as much as possible for speed; this is meant for use with cross-validation or simulations when only the coefficients are needed. Defaults to FALSE.
...	other arguments. Currently ignored.

Details

This function should not be called directly, but through the generic functions `pls` or `mvr` with the argument `method="kernelpls"` (default). Kernel PLS is particularly efficient when the number of objects is (much) larger than the number of variables. The results are equal to the NIPALS algorithm. Several different forms of kernel PLS have been described in literature, e.g. by De Jong and Ter Braak, and two algorithms by Dayal and MacGregor. This function implements the fastest of the latter, not calculating the crossproduct matrix of X. In the Dyal & MacGregor paper, this is "algorithm 1".

Value

A list containing the following components is returned:

coefficients	an array of regression coefficients for 1, ..., ncomp components. The dimensions of coefficients are $c(nvar, npred, ncomp)$ with <code>nvar</code> the number of X variables and <code>npred</code> the number of variables to be predicted in Y.
scores	a matrix of scores.
loadings	a matrix of loadings.
loading.weights	a matrix of loading weights.
Yscores	a matrix of Y-scores.
Yloadings	a matrix of Y-loadings.
projection	the projection matrix used to convert X to scores.

Xmeans	a vector of means of the X variables.
Ymeans	a vector of means of the Y variables.
fitted.values	an array of fitted values. The dimensions of fitted.values are c(nobj, npred, ncomp) with nobj the number samples and npred the number of Y variables.
residuals	an array of regression residuals. It has the same dimensions as fitted.values.
Xvar	a vector with the amount of X-variance explained by each number of components.
Xtotvar	Total variance in X.

If stripped is TRUE, only the components coefficients, Xmeans and Ymeans are returned.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

- de Jong, S. and ter Braak, C. J. F. (1994) Comments on the PLS kernel algorithm. *Journal of Chemometrics*, **8**, 169–174.
- Dayal, B. S. and MacGregor, J. F. (1997) Improved PLS algorithms. *Journal of Chemometrics*, **11**, 73–85.

See Also

[mvr](#) [pls](#) [cppls](#) [pcr](#) [widekernelpls.fit](#) [simpls.fit](#) [oscorespls.fit](#)

mayonnaise

NIR measurements and oil types of mayonnaise

Description

Raw NIR measurements (351 wavelengths, 1100-2500 nm in steps of 4 nm) taken on 54 samples of mayonnaise based on six different oil types (soybean, sunflower, canola, olive, corn, and grapeseed). The resulting 54 samples were measured in triplicates, resulting in $54 \times 3 = 162$ different spectra (120/42 training/test).

Usage

```
data(mayonnaise)
```

Format

A data frame with 162 observations on the following 4 variables.

NIR a matrix with 351 columns

oil.type a numeric vector

design a matrix with 5 columns

train a logical vector

Source

Indahl U, Sahni NS, Kirkhus B, Næs T. Multivariate strategies for classification based on NIR-spectra-with application to mayonnaise. *Chemometr. Intell. Lab. Sys.* 1999; 49: 19-31.

msc

Multiplicative Scatter Correction

Description

Performs multiplicative scatter/signal correction on a data matrix.

Usage

```
msc(X, reference = NULL)
## S3 method for class 'msc'
predict(object, newdata, ...)
## S3 method for class 'msc'
makepredictcall(var, call)
```

Arguments

<code>X</code> , <code>newdata</code>	numeric matrices. The data to scatter correct.
<code>reference</code>	numeric vector. Spectre to use as reference. If NULL, the column means of <code>X</code> are used.
<code>object</code>	an object inheriting from class "msc", normally the result of a call to <code>msc</code> with a single matrix argument.
<code>var</code>	A variable.
<code>call</code>	The term in the formula, as a call.
<code>...</code>	other arguments. Currently ignored.

Details

`makepredictcall.msc` is an internal utility function; it is not meant for interactive use. See [makepredictcall](#) for details.

Value

Both `msc` and `predict.msc` return a multiplicative scatter corrected matrix, with attribute "reference" the vector used as reference spectre. The matrix is given class `c("msc", "matrix")`. For `predict.msc`, the "reference" attribute of `object` is used as reference spectre.

Author(s)

Bjørn-Helge Mevik and Ron Wehrens

References

Martens, H., Næs, T. (1989) *Multivariate calibration*. Chichester: Wiley.

See Also

[mvr](#), [pcr](#), [plsr](#), [stdize](#)

Examples

```
data(yarn)
## Direct correction:
Ztrain <- msc(yarn$NIR[yarn$train,])
Ztest <- predict(Ztrain, yarn$NIR[!yarn$train,])

## Used in formula:
mod <- plsr(density ~ msc(NIR), ncomp = 6, data = yarn[yarn$train,])
pred <- predict(mod, newdata = yarn[!yarn$train,]) # Automatically scatter corrected
```

mvr

Partial Least Squares and Principal Component Regression

Description

Functions to perform partial least squares regression (PLSR), canonical powered partial least squares (CPPLS) or principal component regression (PCR), with a formula interface. Cross-validation can be used. Prediction, model extraction, plot, print and summary methods exist.

Usage

```
mvr(formula, ncomp, Y.add, data, subset, na.action,
    method = pls.options()$mvralg,
    scale = FALSE, validation = c("none", "CV", "LOO"),
    model = TRUE, x = FALSE, y = FALSE, ...)
plsr(..., method = pls.options()$plsralg)
cppls(..., Y.add, weights, method = pls.options()$cpplsalg)
pcr(..., method = pls.options()$pcralg)
```

Arguments

formula	a model formula. Most of the <code>lm</code> formula constructs are supported. See below.
ncomp	the number of components to include in the model (see below).
Y.add	a vector or matrix of additional responses containing relevant information about the observations. Only used for <code>cppls</code> .
data	an optional data frame with the data to fit the model from.
subset	an optional vector specifying a subset of observations to be used in the fitting process.

na.action	a function which indicates what should happen when the data contain missing values. The default is set by the na.action setting of <code>options</code> , and is <code>na.fail</code> if that is unset. The ‘factory-fresh’ default is <code>na.omit</code> . Another possible value is <code>NULL</code> , no action. Value <code>na.exclude</code> can be useful. See <code>na.omit</code> for other alternatives.
method	the multivariate regression method to be used. If <code>"model.frame"</code> , the model frame is returned.
scale	numeric vector, or logical. If numeric vector, X is scaled by dividing each variable with the corresponding element of <code>scale</code> . If <code>scale</code> is <code>TRUE</code> , X is scaled by dividing each variable by its sample standard deviation. If cross-validation is selected, scaling by the standard deviation is done for every segment.
validation	character. What kind of (internal) validation to use. See below.
model	a logical. If <code>TRUE</code> , the model frame is returned.
x	a logical. If <code>TRUE</code> , the model matrix is returned.
y	a logical. If <code>TRUE</code> , the response is returned.
weights	a vector of individual weights for the observations. Only used for <code>cppls</code> . (Optional)
...	additional arguments, passed to the underlying fit functions, and <code>mvrCv</code> .

Details

The functions fit PLSR, CPPLS or PCR models with 1, ..., `ncomp` number of components. Multi-response models are fully supported.

The type of model to fit is specified with the `method` argument. Four PLSR algorithms are available: the kernel algorithm (`"kernelpls"`), the wide kernel algorithm (`"widekernelpls"`), SIMPLS (`"simpls"`) and the classical orthogonal scores algorithm (`"oscorespls"`). One CPPLS algorithm is available (`"cppls"`) providing several extensions to PLS. One PCR algorithm is available: using the singular value decomposition (`"svdpc"`). If `method` is `"model.frame"`, the model frame is returned. The functions `pcr`, `pls` and `cppls` are wrappers for `mvr`, with different values for `method`.

The `formula` argument should be a symbolic formula of the form `response ~ terms`, where `response` is the name of the response vector or matrix (for multi-response models) and `terms` is the name of one or more predictor matrices, usually separated by `+`, e.g., `water ~ FTIR` or `y ~ X + Z`. See [lm](#) for a detailed description. The named variables should exist in the supplied data data frame or in the global environment. Note: Do not use `mvr(mydata$y ~ mydata$X, ...)`, instead use `mvr(y ~ X, data = mydata, ...)`. Otherwise, `predict.mvr` will not work properly. The chapter ‘Statistical models in R’ of the manual ‘An Introduction to R’ distributed with R is a good reference on formulas in R.

The number of components to fit is specified with the argument `ncomp`. If this is not supplied, the maximal number of components is used (taking account of any cross-validation).

If `validation = "CV"`, cross-validation is performed. The number and type of cross-validation segments are specified with the arguments `segments` and `segment.type`. See `mvrCv` for details. If `validation = "LOO"`, leave-one-out cross-validation is performed. It is an error to specify the segments when `validation = "LOO"` is specified.

Note that the cross-validation is optimised for speed, and some generality has been sacrificed. Especially, the model matrix is calculated only once for the complete cross-validation, so models like $y \sim \text{msc}(X)$ will not be properly cross-validated. However, scaling requested by `scale = TRUE` is properly cross-validated. For proper cross-validation of models where the model matrix must be updated/regenerated for each segment, use the separate function [crossval](#).

Value

If `method = "model.frame"`, the model frame is returned. Otherwise, an object of class `mvr` is returned. The object contains all components returned by the underlying fit function. In addition, it contains the following components:

<code>validation</code>	if validation was requested, the results of the cross-validation. See mvrCv for details.
<code>na.action</code>	if observations with missing values were removed, <code>na.action</code> contains a vector with their indices. The class of this vector is used by functions like <code>fitted</code> to decide how to treat the observations.
<code>ncomp</code>	the number of components of the model.
<code>method</code>	the method used to fit the model. See the argument <code>method</code> for possible values.
<code>scale</code>	if scaling was requested (with <code>scale</code>), the scaling used.
<code>call</code>	the function call.
<code>terms</code>	the model terms.
<code>model</code>	if <code>model = TRUE</code> , the model frame.
<code>x</code>	if <code>x = TRUE</code> , the model matrix.
<code>y</code>	if <code>y = TRUE</code> , the model response.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

Martens, H., Næs, T. (1989) *Multivariate calibration*. Chichester: Wiley.

See Also

[kernelpls.fit](#), [widekernelpls.fit](#), [simpls.fit](#), [oscorespls.fit](#), [cppls.fit](#), [svdpc.fit](#), [mvrCv](#), [crossval](#), [loadings](#), [scores](#), [loading.weights](#), [coef.mvr](#), [predict.mvr](#), [R2](#), [MSEP](#), [RMSEP](#), [plot.mvr](#)

Examples

```
data(yarn)
## Default methods:
yarn.pcr <- pcr(density ~ NIR, 6, data = yarn, validation = "CV")
yarn.pls <- plsr(density ~ NIR, 6, data = yarn, validation = "CV")
yarn.cppls <- cppls(density ~ NIR, 6, data = yarn, validation = "CV")
```

```
## Alternative methods:
yarn.oscorespls <- mvr(density ~ NIR, 6, data = yarn, validation = "CV",
  method = "oscorespls")
yarn.simpls <- mvr(density ~ NIR, 6, data = yarn, validation = "CV",
  method = "simpls")

data(oliveoil)
sens.pcr <- pcr(sensory ~ chemical, ncomp = 4, scale = TRUE, data = oliveoil)
sens.pls <- pls(sensory ~ chemical, ncomp = 4, scale = TRUE, data = oliveoil)

## Classification
# A classification example utilizing additional response information
# (Y.add) is found in the cppls.fit manual ('See also' above).
```

mvrCv

Cross-validation

Description

Performs the cross-validation calculations for mvr.

Usage

```
mvrCv(X, Y, ncomp, Y.add = NULL, weights = NULL,
  method = pls.options()$mvralg, scale = FALSE,
  segments = 10, segment.type = c("random", "consecutive", "interleaved"),
  length.seg, jackknife = FALSE, trace = FALSE, ...)
```

Arguments

X	a matrix of observations. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
Y.add	a vector or matrix of additional responses containing relevant information about the observations. Only used for cppls.
weights	a vector of individual weights for the observations. Only used for cppls. (Optional)
method	the multivariate regression method to be used.
scale	logical. If TRUE, the learning X data for each segment is scaled by dividing each variable by its sample standard deviation. The prediction data is scaled by the same amount.
segments	the number of segments to use, or a list with segments (see below).
segment.type	the type of segments to use. Ignored if segments is a list.
length.seg	Positive integer. The length of the segments to use. If specified, it overrides segments unless segments is a list.

jackknife	logical. Whether jackknifing of regression coefficients should be performed.
trace	logical; if TRUE, the segment number is printed for each segment.
...	additional arguments, sent to the underlying fit function.

Details

This function is not meant to be called directly, but through the generic functions `pcr`, `pls`, `cppls` or `mvr` with the argument `validation` set to "CV" or "LOO". All arguments to `mvrCv` can be specified in the generic function call.

If `segments` is a list, the arguments `segment.type` and `length.seg` are ignored. The elements of the list should be integer vectors specifying the indices of the segments. See [cvsegments](#) for details.

Otherwise, segments of type `segment.type` are generated. How many segments to generate is selected by specifying the number of segments in `segments`, or giving the segment length in `length.seg`. If both are specified, `segments` is ignored.

If `jackknife` is TRUE, jackknifed regression coefficients are returned, which can be used for variance estimation ([var.jack](#)) or hypothesis testing ([jack.test](#)).

X and Y do not need to be centered.

Note that this function cannot be used in situations where X needs to be recalculated for each segment (except for scaling by the standard deviation), for instance with `msc` or other preprocessing. For such models, use the more general (but slower) function [crossval](#).

Also note that if needed, the function will silently(!) reduce `ncomp` to the maximal number of components that can be cross-validated, which is $n - l - 1$, where n is the number of observations and l is the length of the longest segment. The (possibly reduced) number of components is returned as the component `ncomp`.

Value

A list with the following components:

<code>method</code>	equals "CV" for cross-validation.
<code>pred</code>	an array with the cross-validated predictions.
<code>coefficients</code>	(only if <code>jackknife</code> is TRUE) an array with the jackknifed regression coefficients. The dimensions correspond to the predictors, responses, number of components, and segments, respectively.
<code>PRESS0</code>	a vector of PRESS values (one for each response variable) for a model with zero components, i.e., only the intercept.
<code>PRESS</code>	a matrix of PRESS values for models with $1, \dots, ncomp$ components. Each row corresponds to one response variable.
<code>adj</code>	a matrix of adjustment values for calculating bias corrected MSE. MSE uses this.
<code>segments</code>	the list of segments used in the cross-validation.
<code>ncomp</code>	the actual number of components used.
<code>gamma</code>	if method <code>cppls</code> is used, gamma values for the powers of each CV segment are returned.

Note

The PRESS0 is always cross-validated using leave-one-out cross-validation. This usually makes little difference in practice, but should be fixed for correctness.

The current implementation of the jackknife stores all jackknife-replicates of the regression coefficients, which can be very costly for large matrices. This might change in a future version.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

Mevik, B.-H., Cederkvist, H. R. (2004) Mean Squared Error of Prediction (MSEP) Estimates for Principal Component Regression (PCR) and Partial Least Squares Regression (PLSR). *Journal of Chemometrics*, **18**(9), 422–429.

See Also

[mvr](#) [crossval](#) [cvsegments](#) [MSEP](#) [var](#) [jack](#) [jack.test](#)

Examples

```
data(yarn)
yarn.pcr <- pcr(density ~ NIR, 6, data = yarn, validation = "CV", segments = 10)
## Not run: plot(MSEP(yarn.pcr))
```

mvrVal

MSEP, RMSEP and R2 of PLSR and PCR models

Description

Functions to estimate the mean squared error of prediction (MSEP), root mean squared error of prediction (RMSEP) and R^2 (A.K.A. coefficient of multiple determination) for fitted PCR and PLSR models. Test-set, cross-validation and calibration-set estimates are implemented.

Usage

```
MSEP(object, ...)
## S3 method for class 'mvr'
MSEP(object, estimate, newdata, ncomp = 1:object$ncomp, comps,
      intercept = cumulative, se = FALSE, ...)

RMSEP(object, ...)
## S3 method for class 'mvr'
RMSEP(object, ...)

R2(object, ...)
```

```
## S3 method for class 'mvr'
R2(object, estimate, newdata, ncomp = 1:object$ncomp, comps,
    intercept = cumulative, se = FALSE, ...)

mvrValstats(object, estimate, newdata, ncomp = 1:object$ncomp, comps,
    intercept = cumulative, se = FALSE, ...)
```

Arguments

object	an mvr object
estimate	a character vector. Which estimators to use. Should be a subset of <code>c("all", "train", "CV", "adjCV", "test")</code> . "adjCV" is only available for (R)MSEP. See below for how the estimators are chosen.
newdata	a data frame with test set data.
ncomp, comps	a vector of positive integers. The components or number of components to use. See below.
intercept	logical. Whether estimates for a model with zero components should be returned as well.
se	logical. Whether estimated standard errors of the estimates should be calculated. Not implemented yet.
...	further arguments sent to underlying functions or (for RMSEP) to MSEP

Details

RMSEP simply calls MSEP and takes the square root of the estimates. It therefore accepts the same arguments as MSEP.

Several estimators can be used. "train" is the training or calibration data estimate, also called (R)MSEC. For R2, this is the unadjusted R^2 . It is overoptimistic and should not be used for assessing models. "CV" is the cross-validation estimate, and "adjCV" (for RMSEP and MSEP) is the bias-corrected cross-validation estimate. They can only be calculated if the model has been cross-validated. Finally, "test" is the test set estimate, using newdata as test set.

Which estimators to use is decided as follows (see below for mvrValstats). If estimate is not specified, the test set estimate is returned if newdata is specified, otherwise the CV and adjusted CV (for RMSEP and MSEP) estimates if the model has been cross-validated, otherwise the training data estimate. If estimate is "all", all possible estimates are calculated. Otherwise, the specified estimates are calculated.

Several model sizes can also be specified. If comps is missing (or is NULL), `length(ncomp)` models are used, with `ncomp[1]` components, ..., `ncomp[length(ncomp)]` components. Otherwise, a single model with the components `comps[1]`, ..., `comps[length(comps)]` is used. If intercept is TRUE, a model with zero components is also used (in addition to the above).

The R^2 values returned by "R2" are calculated as $1 - SSE/SST$, where SST is the (corrected) total sum of squares of the response, and SSE is the sum of squared errors for either the fitted values (i.e., the residual sum of squares), test set predictions or cross-validated predictions (i.e., the *PRESS*). For `estimate = "train"`, this is equivalent to the squared correlation between the fitted values and the response. For `estimate = "train"`, the estimate is often called the prediction R^2 .

mvrValstats is a utility function that calculates the statistics needed by MSEP and R2. It is not intended to be used interactively. It accepts the same arguments as MSEP and R2. However, the estimate argument must be specified explicitly: no partial matching and no automatic choice is made. The function simply calculates the types of estimates it knows, and leaves the other untouched.

Value

mvrValstats returns a list with components

SSE three-dimensional array of SSE values. The first dimension is the different estimators, the second is the response variables and the third is the models.

SST matrix of SST values. The first dimension is the different estimators and the second is the response variables.

nobj a numeric vector giving the number of objects used for each estimator.

comps the components specified, with 0 prepended if intercept is TRUE.

cumulative TRUE if comps was NULL or not specified.

The other functions return an object of class "mvrVal", with components

val three-dimensional array of estimates. The first dimension is the different estimators, the second is the response variables and the third is the models.

type "MSEP", "RMSEP" or "R2".

comps the components specified, with 0 prepended if intercept is TRUE.

cumulative TRUE if comps was NULL or not specified.

call the function call

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

Mevik, B.-H., Cederkvist, H. R. (2004) Mean Squared Error of Prediction (MSEP) Estimates for Principal Component Regression (PCR) and Partial Least Squares Regression (PLSR). *Journal of Chemometrics*, **18**(9), 422–429.

See Also

[mvr](#), [crossval](#), [mvrCv](#), [validationplot](#), [plot.mvrVal](#)

Examples

```
data(oliveoil)
mod <- pls(sensory ~ chemical, ncomp = 4, data = oliveoil, validation = "LOO")
RMSEP(mod)
## Not run: plot(R2(mod))
```

`oliveoil`*Sensory and physico-chemical data of olive oils*

Description

A data set with scores on 6 attributes from a sensory panel and measurements of 5 physico-chemical quality parameters on 16 olive oil samples. The first five oils are Greek, the next five are Italian and the last six are Spanish.

Usage`oliveoil`**Format**

A data frame with 16 observations on the following 2 variables.

`sensory` a matrix with 6 columns. Scores for attributes ‘yellow’, ‘green’, ‘brown’, ‘glossy’, ‘transp’, and ‘syrup’.

`chemical` a matrix with 5 columns. Measurements of acidity, peroxide, K232, K270, and DK.

Source

Massart, D. L., Vandeginste, B. G. M., Buydens, L. M. C., de Jong, S., Lewi, P. J., Smeyers-Verbeke, J. (1998) *Handbook of Chemometrics and Qualimetrics: Part B*. Elsevier. Tables 35.1 and 35.4.

`oscorespls.fit`*Orthogonal scores PLSR*

Description

Fits a PLSR model with the orthogonal scores algorithm (aka the NIPALS algorithm).

Usage

```
oscorespls.fit(X, Y, ncomp, stripped = FALSE,  
              tol = .Machine$double.eps^0.5, ...)
```

Arguments

X	a matrix of observations. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
stripped	logical. If TRUE the calculations are stripped as much as possible for speed; this is meant for use with cross-validation or simulations when only the coefficients are needed. Defaults to FALSE.
tol	numeric. The tolerance used for determining convergence in multi-response models.
...	other arguments. Currently ignored.

Details

This function should not be called directly, but through the generic functions `pls` or `mvr` with the argument `method="oscorespls"`. It implements the orthogonal scores algorithm, as described in *Martens and Næs (1989)*. This is one of the two “classical” PLSR algorithms, the other being the orthogonal loadings algorithm.

Value

A list containing the following components is returned:

coefficients	an array of regression coefficients for 1, ..., ncomp components. The dimensions of coefficients are $c(\text{nvar}, \text{npred}, \text{ncomp})$ with <code>nvar</code> the number of X variables and <code>npred</code> the number of variables to be predicted in Y.
scores	a matrix of scores.
loadings	a matrix of loadings.
loading.weights	a matrix of loading weights.
Yscores	a matrix of Y-scores.
Yloadings	a matrix of Y-loadings.
projection	the projection matrix used to convert X to scores.
Xmeans	a vector of means of the X variables.
Ymeans	a vector of means of the Y variables.
fitted.values	an array of fitted values. The dimensions of <code>fitted.values</code> are $c(\text{nobj}, \text{npred}, \text{ncomp})$ with <code>nobj</code> the number samples and <code>npred</code> the number of Y variables.
residuals	an array of regression residuals. It has the same dimensions as <code>fitted.values</code> .
Xvar	a vector with the amount of X-variance explained by each number of components.
Xtotvar	Total variance in X.

If `stripped` is TRUE, only the components `coefficients`, `Xmeans` and `Ymeans` are returned.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

Martens, H., Næs, T. (1989) *Multivariate calibration*. Chichester: Wiley.

See Also

[mvr](#) [pls](#) [pcr](#) [kernelpls.fit](#) [widekernelpls.fit](#) [simpls.fit](#)

plot.mvr

Plot Method for MVR objects

Description

plot.mvr plots predictions, coefficients, scores, loadings, biplots, correlation loadings or validation plots (RMSEP curves, etc.).

Usage

```
## S3 method for class 'mvr'
plot(x, plottype = c("prediction", "validation", "coefficients",
                    "scores", "loadings", "biplot", "correlation"), ...)
```

Arguments

x an object of class mvr. The fitted model to plot.
 plottype character. What kind of plot to plot.
 ... further arguments, sent to the underlying plot functions.

Details

The function is simply a wrapper for the underlying plot functions used to make the selected plots. See [predplot.mvr](#), [validationplot](#), [coefplot](#), [scoreplot](#), [loadingplot](#), [biplot.mvr](#) or [corrplot](#) for details. Note that all arguments except x and plottype must be named.

Value

plot.mvr returns whatever the underlying plot function returns.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [predplot.mvr](#), [validationplot](#), [coefplot](#), [scoreplot](#), [loadingplot](#), [biplot.mvr](#), [corrplot](#)

Examples

```

data(yarn)
nir.pcr <- pcr(density ~ NIR, ncomp = 9, data = yarn, validation = "CV")
## Not run:
plot(nir.pcr, ncomp = 5) # Plot of cross-validated predictions
plot(nir.pcr, "scores") # Score plot
plot(nir.pcr, "loadings", comps = 1:3) # The three first loadings
plot(nir.pcr, "coef", ncomp = 5) # Coefficients
plot(nir.pcr, "val") # RMSEP curves
plot(nir.pcr, "val", val.type = "MSEP", estimate = "CV") # CV MSEP

## End(Not run)

```

pls.options

Set or return options for the pls package

Description

A function to set options for the **pls** package, or to return the current options.

Usage

```
pls.options(...)
```

Arguments

... a single list, a single character vector, or any number of named arguments (*name = value*).

Details

If called with no arguments, or with an empty list as the single argument, `pls.options` returns the current options.

If called with a character vector as the single argument, a list with the arguments named in the vector are returned.

If called with a non-empty list as the single arguments, the list elements should be named, and are treated as named arguments to the function.

Otherwise, `pls.options` should be called with one or more named arguments *name = value*. For each argument, the option named *name* will be given the value *value*.

The options are saved in a variable `.pls.Options` in the global environment, and remain in effect until the end of the session. If the environment is saved upon exit, they will be remembered in the next session. The ‘factory defaults’ can be restored by removing `.pls.Options` from the global environment.

The recognised options are:

mvrAlg The fit method to use in `mvr` and `mvrCv`. The value should be one of the allowed methods. Defaults to "kernelpls". Can be overridden with the argument `method` in `mvr` and `mvrCv`.

pcralg The fit method to use in `pcr`. The value should be one of the allowed methods. Defaults to "svdpc". Can be overridden with the argument `method` in `pcr`.

plsralg The fit method to use in `pls`. The value should be one of the allowed methods. Defaults to "kernelpls". Can be overridden with the argument `method` in `pls`.

cpplsalg The fit method to use in `cppls`. The value should be one of the allowed methods. Defaults to "cppls". Can be overridden with the argument `method` in `cppls`.

w.tol The tolerance used for removing values close to 0 in the vectors of loading weights in `cppls`. Defaults to `.Machine$double.eps`.

X.tol The tolerance used for removing predictor variables with L1 norms close to 0 in `cppls`. Defaults to 10^{-12} .

Value

A list with the (possibly changed) options. If any named argument (or list element) was provided, the list is returned invisibly.

Side Effects

If any named argument (or list element) was provided, `pls.options` updates the elements of the option list `.pls.Options` in the global environment.

Note

The function is a slight modification of the function `sm.options` from the package `sm`.

Author(s)

Bjørn-Helge Mevik and Ron Wehrens

Examples

```
## Return current options:
pls.options()
pls.options("plsralg")
pls.options(c("plsralg", "pcralg"))

## Set options:
pls.options(plsralg = "simpls", mvralg = "simpls")
pls.options(list(plsralg = "simpls", mvralg = "simpls")) # Equivalent
pls.options()

## Restore 'factory settings':
rm(.pls.Options)
pls.options()
```

predict.mvr

Predict Method for PLSR and PCR

Description

Prediction for mvr (PCR, PLSR) models. New responses or scores are predicted using a fitted model and a new matrix of observations.

Usage

```
## S3 method for class 'mvr'
predict(object, newdata, ncomp = 1:object$ncomp, comps,
        type = c("response", "scores"), na.action = na.pass, ...)
```

Arguments

object	an mvr object. The fitted model
newdata	a data frame. The new data. If missing, the training data is used.
ncomp, comps	vector of positive integers. The components to use in the prediction. See below.
type	character. Whether to predict scores or response values
na.action	function determining what should be done with missing values in newdata. The default is to predict NA. See na.omit for alternatives.
...	further arguments. Currently not used

Details

When type is "response" (default), predicted response values are returned. If comps is missing (or is NULL), predictions for `length(ncomp)` models with `ncomp[1]` components, `ncomp[2]` components, etc., are returned. Otherwise, predictions for a single model with the exact components in comps are returned. (Note that in both cases, the intercept is always included in the predictions. It can be removed by subtracting the `Ymeans` component of the fitted model.)

When type is "scores", predicted score values are returned for the components given in comps. If comps is missing or NULL, `ncomps` is used instead.

It is also possible to supply a matrix instead of a data frame as `newdata`, which is then assumed to be the X data matrix. Note that the usual checks for the type of the data are then omitted. Also note that this is *only* possible with `predict`; it will not work in functions like `predplot`, `RMSEP` or `R2`, because they also need the response variable of the new data.

Value

When type is "response", a three dimensional array of predicted response values is returned. The dimensions correspond to the observations, the response variables and the model sizes, respectively.

When type is "scores", a score matrix is returned.

Note

A warning message like ‘newdata’ had 10 rows but variable(s) found have 106 rows’ means that not all variables were found in the newdata data frame. This (usually) happens if the formula contains terms like yarn\$NIR. Do not use such terms; use the data argument instead. See [mvr](#) for details.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [summary.mvr](#), [coef.mvr](#), [plot.mvr](#)

Examples

```
data(yarn)
nir.mvr <- mvr(density ~ NIR, ncomp = 5, data = yarn[yarn$train,])

## Predicted responses for models with 1, 2, 3 and 4 components
pred.resp <- predict(nir.mvr, ncomp = 1:4, newdata = yarn[!yarn$train,])

## Predicted responses for a single model with components 1, 2, 3, 4
predict(nir.mvr, comps = 1:4, newdata = yarn[!yarn$train,])

## Predicted scores
predict(nir.mvr, comps = 1:3, type = "scores", newdata = yarn[!yarn$train,])
```

predplot

Prediction Plots

Description

Functions to plot predicted values against measured values for a fitted model.

Usage

```
predplot(object, ...)
## Default S3 method:
predplot(object, ...)
## S3 method for class 'mvr'
predplot(object, ncomp = object$ncomp, which, newdata, nCols,
         nRows, xlab = "measured", ylab = "predicted", main,
         ..., font.main, cex.main)
predplotXy(x, y, line = FALSE, labels, type = "p", main = "Prediction plot",
          xlab = "measured response", ylab = "predicted response",
          line.col = par("col"), line.lty = NULL, line.lwd = NULL, ...)
```

Arguments

object	a fitted model.
ncomp	integer vector. The model sizes (numbers of components) to use for prediction.
which	character vector. Which types of predictions to plot. Should be a subset of <code>c("train", "validation", "test")</code> . If not specified, <code>plot.mvr</code> selects test set predictions if <code>newdata</code> is supplied, otherwise cross-validated predictions if the model has been cross-validated, otherwise fitted values from the calibration data.
newdata	data frame. New data to predict.
nCols, nRows	integer. The number of columns and rows the plots will be laid out in. If not specified, <code>plot.mvr</code> tries to be intelligent.
xlab, ylab	titles for <i>x</i> and <i>y</i> axes. Typically character strings, but can be expressions or lists. See title for details.
labels	optional. Alternative plot labels to use. Either a vector of labels, or "names" or "numbers" to use the row names or row numbers of the data as labels.
type	character. What type of plot to make. Defaults to "p" (points). See plot for a complete list of types. The argument is ignored if <code>labels</code> is specified.
main	optional main title for the plot. See Details.
font.main	font to use for main titles. See par for details. Also see Details below.
cex.main	numeric. The magnification to be used for main titles relative to the current size. Also see Details below.
x	numeric vector. The observed response values.
y	numeric vector. The predicted response values.
line	logical. Whether a target line should be drawn.
line.col, line.lty, line.lwd	character or numeric. The <code>col</code> , <code>lty</code> and <code>lwd</code> parameters for the target line. See par for details.
...	further arguments sent to underlying plot functions.

Details

`predplot` is a generic function for plotting predicted versus measured response values, with default and `mvr` methods currently implemented. The default method is very simple, and doesn't handle multiple responses or new data.

The `mvr` method, handles multiple responses, model sizes and types of predictions by making one plot for each combination. It can also be called through the `plot` method for `mvr`, by specifying `plottype = "prediction"` (the default).

The argument `main` can be used to specify the main title of the plot. It is handled in a non-standard way. If there is only one (sub) plot, `main` will be used as the main title of the plot. If there is *more* than one (sub) plot, however, the presence of `main` will produce a corresponding 'global' title on the page. Any graphical parameters, e.g., `cex.main`, supplied to `coefplot` will only affect the 'ordinary' plot titles, not the 'global' one. Its appearance can be changed by setting the parameters with [par](#), which will affect *both* titles (with the exception of `font.main` and `cex.main`, which will

only affect the ‘global’ title when there is more than one plot). (To have different settings for the two titles, one can override the `par` settings with arguments to `predplot`.)

`predplotXy` is an internal function and is not meant for interactive use. It is called by the `predplot` methods, and its arguments, e.g. `line`, can be given in the `predplot` call.

Value

The functions invisibly return a matrix with the (last) plotted data.

Note

The `font.main` and `cex.main` must be (completely) named. This is to avoid that any argument `cex` or `font` matches them.

Tip: If the labels specified with `labels` are too long, they get clipped at the border of the plot region. This can be avoided by supplying the graphical parameter `xpd = TRUE` in the plot call.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [plot.mvr](#)

Examples

```
data(yarn)
mod <- plsr(density ~ NIR, ncomp = 10, data = yarn[yarn$train,], validation = "CV")
## Not run:
predplot(mod, ncomp = 1:6)
plot(mod, ncomp = 1:6) # Equivalent to the previous
## Both cross-validated and test set predictions:
predplot(mod, ncomp = 4:6, which = c("validation", "test"),
         newdata = yarn[!yarn$train,])

## End(Not run)

data(oliveoil)
mod.sens <- plsr(sensory ~ chemical, ncomp = 4, data = oliveoil)
## Not run: plot(mod.sens, ncomp = 2:4) # Several responses gives several plots
```

scoreplot

Plots of Scores, Loadings and Correlation Loadings

Description

Functions to make scatter plots of scores or correlation loadings, and scatter or line plots of loadings.

Usage

```

scoreplot(object, ...)
## Default S3 method:
scoreplot(object, comps = 1:2, labels, identify = FALSE, type = "p",
           xlab, ylab, ...)
## S3 method for class 'scores'
plot(x, ...)

loadingplot(object, ...)
## Default S3 method:
loadingplot(object, comps = 1:2, scatter = FALSE, labels,
            identify = FALSE, type, lty, lwd = NULL, pch, cex = NULL,
            col, legendpos, xlab, ylab, pretty.xlabels = TRUE, xlim, ...)
## S3 method for class 'loadings'
plot(x, ...)

corrplot(object, comps = 1:2, labels, radii = c(sqrt(1/2), 1),
         identify = FALSE, type = "p", xlab, ylab, ...)

```

Arguments

<code>object</code>	an R object. The fitted model.
<code>comps</code>	integer vector. The components to plot.
<code>scatter</code>	logical. Whether the loadings should be plotted as a scatter instead of as lines.
<code>labels</code>	optional. Alternative plot labels or x axis labels. See Details.
<code>radii</code>	numeric vector, giving the radii of the circles drawn in <code>corrplot</code> . The default radii represent 50% and 100% explained variance of the X variables by the chosen components.
<code>identify</code>	logical. Whether to use <code>identify</code> to interactively identify points. See below.
<code>type</code>	character. What type of plot to make. Defaults to "p" (points) for scatter plots and "l" (lines) for line plots. See plot for a complete list of types (not all types are possible/meaningful for all plots).
<code>lty</code>	vector of line types (recycled as necessary). Line types can be specified as integers or character strings (see par for the details).
<code>lwd</code>	vector of positive numbers (recycled as necessary), giving the width of the lines.
<code>pch</code>	plot character. A character string or a vector of single characters or integers (recycled as necessary). See points for all alternatives.
<code>cex</code>	numeric vector of character expansion sizes (recycled as necessary) for the plotted symbols.
<code>col</code>	character or integer vector of colors for plotted lines and symbols (recycled as necessary). See par for the details.
<code>legendpos</code>	Legend position. Optional. Ignored if <code>scatter</code> is TRUE. If present, a legend is drawn at the given position. The position can be specified symbolically (e.g.,

	legendpos = "topright"). This requires R \geq 2.1.0. Alternatively, the position can be specified explicitly (legendpos = t(c(x,y))) or interactively (legendpos = locator()).
xlab,ylab	titles for x and y axes. Typically character strings, but can be expressions or lists. See title for details.
pretty.xlabels	logical. If TRUE, loadingplot tries to plot the x labels more nicely. See Details.
xlim	optional vector of length two, with the x limits of the plot.
x	a scores or loadings object. The scores or loadings to plot.
...	further arguments sent to the underlying plot function(s).

Details

plot.scores is simply a wrapper calling scoreplot, passing all arguments. Similarly for plot.loadings.

scoreplot is generic, currently with a default method that works for matrices and any object for which scores returns a matrix. The default scoreplot method makes one or more scatter plots of the scores, depending on how many components are selected. If one or two components are selected, and identify is TRUE, the function identify is used to interactively identify points.

Also loadingplot is generic, with a default method that works for matrices and any object where loadings returns a matrix. If scatter is TRUE, the default method works exactly like the default scoreplot method. Otherwise, it makes a lineplot of the selected loading vectors, and if identify is TRUE, uses identify to interactively identify points. Also, if legendpos is given, a legend is drawn at the position indicated.

corrplot works exactly like the default scoreplot method, except that at least two components must be selected. The “correlation loadings”, i.e. the correlations between each variable and the selected components (see References), are plotted as pairwise scatter plots, with concentric circles of radii given by radii. Each point corresponds to an X variable. The squared distance between the point and origin equals the fraction of the variance of the variable explained by the components in the panel. The default radii corresponds to 50% and 100% explained variance.

scoreplot, loadingplot and corrplot can also be called through the plot method for mvr objects, by specifying plottype as “scores”, “loadings” or “correlation”, respectively. See [plot.mvr](#).

The argument labels can be a vector of labels or one of “names” and “numbers”.

If a scatter plot is produced (i.e., scoreplot, corrplot, or loadingplot with scatter = TRUE), the labels are used instead of plot symbols for the points plotted. If labels is “names” or “numbers”, the row names or row numbers of the matrix (scores, loadings or correlation loadings) are used.

If a line plot is produced (i.e., loadingplot), the labels are used as x axis labels. If labels is “names” or “numbers”, the variable names are used as labels, the difference being that with “numbers”, the variable names are converted to numbers, if possible. Variable names of the forms “number” or “number text” (where the space is optional), are handled.

The argument pretty.xlabels is only used when labels is specified for a line plot. If TRUE (default), the code tries to use a ‘pretty’ selection of labels. If labels is “numbers”, it also uses the numerical values of the labels for horizontal spacing. If one has excluded parts of the spectral region, one might therefore want to use pretty.xlabels = FALSE.

Value

The functions return whatever the underlying plot function (or `identify`) returns.

Note

[legend](#) has many options. If you want greater control over the appearance of the legend, omit the `legendpos` argument and call `legend` manually.

Graphical parameters (such as `pch` and `cex`) can also be used with `scoreplot` and `corrplot`. They are not listed in the argument list simply because they are not handled specifically in the function (unlike in `loadingplot`), but passed directly to the underlying plot functions by

Tip: If the labels specified with `labels` are too long, they get clipped at the border of the plot region. This can be avoided by supplying the graphical parameter `xpd = TRUE` in the plot call.

The handling of `labels` and `pretty.xlabels` in `coefplot` is experimental.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

Martens, H., Martens, M. (2000) Modified Jack-knife Estimation of Parameter Uncertainty in Bilinear Modelling by Partial Least Squares Regression (PLSR). *Food Quality and Preference*, **11**(1–2), 5–16.

See Also

[mvr](#), [plot.mvr](#), [scores](#), [loadings](#), [identify](#), [legend](#)

Examples

```
data(yarn)
mod <- plsrdensity ~ NIR, ncomp = 10, data = yarn)
## These three are equivalent:
## Not run:
scoreplot(mod, comps = 1:5)
plot(scores(mod), comps = 1:5)
plot(mod, plottype = "scores", comps = 1:5)

loadingplot(mod, comps = 1:5)
loadingplot(mod, comps = 1:5, legendpos = "topright") # With legend
loadingplot(mod, comps = 1:5, scatter = TRUE) # Plot as scatterplots

corrplot(mod, comps = 1:2)
corrplot(mod, comps = 1:3)

## End(Not run)
```

`scores`*Extract Scores and Loadings from PLSR and PCR Models*

Description

These functions extract score and loading matrices from fitted `mvr` models.

Usage

```
scores(object, ...)  
## Default S3 method:  
scores(object, ...)  
  
loadings(object, ...)  
## Default S3 method:  
loadings(object, ...)  
  
loading.weights(object)  
  
Yscores(object)  
  
Yloadings(object)
```

Arguments

<code>object</code>	a fitted model to extract from.
<code>...</code>	extra arguments, currently not used.

Details

All functions extract the indicated matrix from the fitted model, and will work with any object having a suitably named component.

The default scores and loadings methods also handle `prcomp` objects (their scores and loadings components are called `x` and `rotation`, resp.), and add an attribute `"explvar"` with the variance explained by each component, if this is available. (See [explvar](#) for details.)

Value

A matrix with scores or loadings.

Note

There is a `loadings` function in package **stats**. It simply returns any element named `"loadings"`. See [loadings](#) for details. The function can be accessed as `stats::loadings(...)`.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [coef.mvr](#)

Examples

```
data(yarn)
plsmod <- pls(density ~ NIR, 6, data = yarn)
scores(plsmod)
loadings(plsmod)[,1:4]
```

simpls.fit

Sijmen de Jong's SIMPLS

Description

Fits a PLSR model with the SIMPLS algorithm.

Usage

```
simpls.fit(X, Y, ncomp, stripped = FALSE, ...)
```

Arguments

X	a matrix of observations. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
stripped	logical. If TRUE the calculations are stripped as much as possible for speed; this is meant for use with cross-validation or simulations when only the coefficients are needed. Defaults to FALSE.
...	other arguments. Currently ignored.

Details

This function should not be called directly, but through the generic functions `pls` or `mvr` with the argument `method="simpls"`. SIMPLS is much faster than the NIPALS algorithm, especially when the number of X variables increases, but gives slightly different results in the case of multivariate Y. SIMPLS truly maximises the covariance criterion. According to de Jong, the standard PLS2 algorithms lie closer to ordinary least-squares regression where a precise fit is sought; SIMPLS lies closer to PCR with stable predictions.

Value

A list containing the following components is returned:

coefficients	an array of regression coefficients for 1, . . . , ncomp components. The dimensions of coefficients are c(nvar, npred, ncomp) with nvar the number of X variables and npred the number of variables to be predicted in Y.
scores	a matrix of scores.
loadings	a matrix of loadings.
Yscores	a matrix of Y-scores.
Yloadings	a matrix of Y-loadings.
projection	the projection matrix used to convert X to scores.
Xmeans	a vector of means of the X variables.
Ymeans	a vector of means of the Y variables.
fitted.values	an array of fitted values. The dimensions of fitted.values are c(nobj, npred, ncomp) with nobj the number samples and npred the number of Y variables.
residuals	an array of regression residuals. It has the same dimensions as fitted.values.
Xvar	a vector with the amount of X-variance explained by each number of components.
Xtotvar	Total variance in X.

If stripped is TRUE, only the components coefficients, Xmeans and Ymeans are returned.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

de Jong, S. (1993) SIMPLS: an alternative approach to partial least squares regression. *Chemometrics and Intelligent Laboratory Systems*, **18**, 251–263.

See Also

[mvr](#) [pls](#) [pcr](#) [kernelpls.fit](#) [widekernelpls.fit](#) [oscorespls.fit](#)

 stdize *Standardization of Data Matrices*

Description

Performs standardization (centering and scaling) of a data matrix.

Usage

```
stdize(x, center = TRUE, scale = TRUE)
## S3 method for class 'stdized'
predict(object, newdata, ...)
## S3 method for class 'stdized'
makepredictcall(var, call)
```

Arguments

x, newdata	numeric matrices. The data to standardize.
center	logical value or numeric vector of length equal to the number of columns of x.
scale	logical value or numeric vector of length equal to the number of columns of x.
object	an object inheriting from class "stdized", normally the result of a call to stdize.
var	A variable.
call	The term in the formula, as a call.
...	other arguments. Currently ignored.

Details

makepredictcall.stdized is an internal utility function; it is not meant for interactive use. See [makepredictcall](#) for details.

If center is TRUE, x is centered by subtracting the column mean from each column. If center is a numeric vector, it is used in place of the column means.

If scale is TRUE, x is scaled by dividing each column by its sample standard deviation. If scale is a numeric vector, it is used in place of the standard deviations.

Value

Both stdize and predict.stdized return a scaled and/or centered matrix, with attributes "stdized:center" and/or "stdized:scale" the vector used for centering and/or scaling. The matrix is given class c("stdized", "matrix").

Note

stdize is very similar to [scale](#). The difference is that when scale = TRUE, stdize divides the columns by their standard deviation, while scale uses the root-mean-square of the columns. If center is TRUE, this is equivalent, but in general it is not.

Author(s)

Bjørn-Helge Mevik and Ron Wehrens

See Also

[mvr](#), [pcr](#), [pls](#), [msc](#), [scale](#)

Examples

```
data(yarn)
## Direct standardization:
Ztrain <- stdize(yarn$NIR[yarn$train,])
Ztest <- predict(Ztrain, yarn$NIR[!yarn$train,])

## Used in formula:
mod <- pls(density ~ stdize(NIR), ncomp = 6, data = yarn[yarn$train,])
pred <- predict(mod, newdata = yarn[!yarn$train,]) # Automatically standardized
```

summary.mvr

Summary and Print Methods for PLSR and PCR objects

Description

Summary and print methods for `mvr` and `mvrVal` objects.

Usage

```
## S3 method for class 'mvr'
summary(object, what = c("all", "validation", "training"),
        digits = 4, print.gap = 2, ...)
## S3 method for class 'mvr'
print(x, ...)
## S3 method for class 'mvrVal'
print(x, digits = 4, print.gap = 2, ...)
```

Arguments

<code>x</code> , <code>object</code>	an <code>mvr</code> object
<code>what</code>	one of "all", "validation" or "training"
<code>digits</code>	integer. Minimum number of significant digits in the output. Default is 4.
<code>print.gap</code>	Integer. Gap between columns of the printed tables.
<code>...</code>	Other arguments sent to underlying methods.

Details

If `what` is "training", the explained variances are given; if it is "validation", the cross-validated RMSEPs (if available) are given; if it is "all", both are given.

Value

print.mvr and print.mvrVal return the object invisibly.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [pcr](#), [plsr](#), [RMSEP](#), [MSEP](#)

Examples

```
data(yarn)
nir.mvr <- mvr(density ~ NIR, ncomp = 8, validation = "LOO", data = yarn)
nir.mvr
summary(nir.mvr)
RMSEP(nir.mvr)
```

svdpc.fit

Principal Component Regression

Description

Fits a PCR model using the singular value decomposition.

Usage

```
svdpc.fit(X, Y, ncomp, stripped = FALSE, ...)
```

Arguments

X	a matrix of observations. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
stripped	logical. If TRUE the calculations are stripped as much as possible for speed; this is meant for use with cross-validation or simulations when only the coefficients are needed. Defaults to FALSE.
...	other arguments. Currently ignored.

Details

This function should not be called directly, but through the generic functions `pcr` or `mvr` with the argument `method="svdpc"`. The singular value decomposition is used to calculate the principal components.

Value

A list containing the following components is returned:

coefficients	an array of regression coefficients for 1, ..., ncomp components. The dimensions of coefficients are c(nvar, npred, ncomp) with nvar the number of X variables and npred the number of variables to be predicted in Y.
scores	a matrix of scores.
loadings	a matrix of loadings.
Yloadings	a matrix of Y-loadings.
projection	the projection matrix used to convert X to scores.
Xmeans	a vector of means of the X variables.
Ymeans	a vector of means of the Y variables.
fitted.values	an array of fitted values. The dimensions of fitted.values are c(nobj, npred, ncomp) with nobj the number samples and npred the number of Y variables.
residuals	an array of regression residuals. It has the same dimensions as fitted.values.
Xvar	a vector with the amount of X-variance explained by each number of components.
Xtotvar	Total variance in X.

If stripped is TRUE, only the components coefficients, Xmeans and Ymeans are returned.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

References

Martens, H., Næs, T. (1989) *Multivariate calibration*. Chichester: Wiley.

See Also

[mvr](#) [pls](#) [pcr](#) [cppls](#)

validationplot

Validation Plots

Description

Functions to plot validation statistics, such as RMSEP or R^2 , as a function of the number of components.

Usage

```
validationplot(object, val.type = c("RMSEP", "MSEP", "R2"), estimate,
               newdata, ncomp, comps, intercept, ...)
## S3 method for class 'mvrVal'
plot(x, nCols, nRows, type = "l", lty = 1:nEst, lwd = NULL,
     pch = 1:nEst, cex = NULL, col = 1:nEst, legendpos,
     xlab = "number of components", ylab = x$type, main, ...)
```

Arguments

<code>object</code>	an <code>mvr</code> object.
<code>val.type</code>	character. What type of validation statistic to plot.
<code>estimate</code>	character. Which estimates of the statistic to calculate. See RMSEP .
<code>newdata</code>	data frame. Optional new data used to calculate statistic.
<code>ncomp, comps</code>	integer vector. The model sizes to compute the statistic for. See RMSEP .
<code>intercept</code>	logical. Whether estimates for a model with zero components should be calculated as well.
<code>x</code>	an <code>mvrVal</code> object. Usually the result of a RMSEP , MSEP or R2 call.
<code>nCols, nRows</code>	integers. The number of columns and rows the plots will be laid out in. If not specified, <code>plot.mvrVal</code> tries to be intelligent.
<code>type</code>	character. What type of plots to create. Defaults to "l" (lines). Alternative types include "p" (points) and "b" (both). See plot for a complete list of types.
<code>lty</code>	vector of line types (recycled as necessary). Line types can be specified as integers or character strings (see par for the details).
<code>lwd</code>	vector of positive numbers (recycled as necessary), giving the width of the lines.
<code>pch</code>	plot character. A character string or a vector of single characters or integers (recycled as necessary). See points for all alternatives.
<code>cex</code>	numeric vector of character expansion sizes (recycled as necessary) for the plotted symbols.
<code>col</code>	character or integer vector of colors for plotted lines and symbols (recycled as necessary). See par for the details.
<code>legendpos</code>	Legend position. Optional. If present, a legend is drawn at the given position. The position can be specified symbolically (e.g., <code>legendpos = "topright"</code>). This requires R \geq 2.1.0. Alternatively, the position can be specified explicitly (<code>legendpos = t(c(x,y))</code>) or interactively (<code>legendpos = locator()</code>). This only works well for plots of single-response models.
<code>xlab, ylab</code>	titles for x and y axes. Typically character strings, but can be expressions (e.g., <code>expression(R^2)</code>) or lists. See title for details.
<code>main</code>	optional main title for the plot. See Details .
<code>...</code>	Further arguments sent to underlying plot functions.

Details

validationplot calls the proper validation function (currently [MSEP](#), [RMSEP](#) or [R2](#)) and plots the results with `plot.mvrVal`. validationplot can be called through the `mvr` plot method, by specifying `plottype = "validation"`.

`plot.mvrVal` creates one plot for each response variable in the model, laid out in a rectangle. It uses [matplot](#) for performing the actual plotting. If `legendpos` is given, a legend is drawn at the given position.

The argument `main` can be used to specify the main title of the plot. It is handled in a non-standard way. If there is only one (sub) plot, `main` will be used as the main title of the plot. If there is *more* than one (sub) plot, however, the presence of `main` will produce a corresponding ‘global’ title on the page. Any graphical parameters, e.g., `cex.main`, supplied to `coefplot` will only affect the ‘ordinary’ plot titles, not the ‘global’ one. Its appearance can be changed by setting the parameters with `par`, which will affect *both* titles. (To have different settings for the two titles, one can override the `par` settings with arguments to the plot function.)

Note

[legend](#) has many options. If you want greater control over the appearance of the legend, omit the `legendpos` argument and call `legend` manually.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[mvr](#), [plot.mvr](#), [RMSEP](#), [MSEP](#), [R2](#), [matplot](#), [legend](#)

Examples

```
data(oliveoil)
mod <- plsr(sensory ~ chemical, data = oliveoil, validation = "LOO")
## Not run:
## These three are equivalent:
validationplot(mod, estimate = "all")
plot(mod, "validation", estimate = "all")
plot(RMSEP(mod, estimate = "all"))
## Plot R2:
plot(mod, "validation", val.type = "R2")
## Plot R2, with a legend:
plot(mod, "validation", val.type = "MSEP", legendpos = "top") # R >= 2.1.0

## End(Not run)
```

var.jack

Jackknife Variance Estimates of Regression Coefficients

Description

Calculates jackknife variance or covariance estimates of regression coefficients.

Usage

```
var.jack(object, ncomp = object$ncomp, covariance = FALSE, use.mean = TRUE)
```

Arguments

object	an mvr object. A cross-validated model fitted with jackknife = TRUE.
ncomp	the number of components to use for estimating the (co)variances
covariance	logical. If TRUE, covariances are calculated; otherwise only variances. The default is FALSE.
use.mean	logical. If TRUE (default), the mean coefficients are used when estimating the (co)variances; otherwise the coefficients from a model fitted to the entire data set. See Details.

Details

The original (Tukey) jackknife variance estimator is defined as $(g - 1)/g \sum_{i=1}^g (\tilde{\beta}_{-i} - \bar{\beta})^2$, where g is the number of segments, $\tilde{\beta}_{-i}$ is the estimated coefficient when segment i is left out (called the jackknife replicates), and $\bar{\beta}$ is the mean of the $\tilde{\beta}_{-i}$. The most common case is delete-one jackknife, with $g = n$, the number of observations.

This is the definition var.jack uses by default.

However, Martens and Martens (2000) defined the estimator as $(g - 1)/g \sum_{i=1}^g (\tilde{\beta}_{-i} - \hat{\beta})^2$, where $\hat{\beta}$ is the coefficient estimate using the entire data set. I.e., they use the original fitted coefficients instead of the mean of the jackknife replicates. Most (all?) other jackknife implementations for PLSR use this estimator. var.jack can be made to use this definition with use.mean = FALSE. In practice, the difference should be small if the number of observations is sufficiently large. Note, however, that all theoretical results about the jackknife refer to the ‘proper’ definition. (Also note that this option might disappear in a future version.)

Value

If covariance is FALSE, an $p \times q \times c$ array of variance estimates, where p is the number of predictors, q is the number of responses, and c is the number of components.

If covariance is TRUE, an $pq \times pq \times c$ array of variance-covariance estimates.

Warning

Note that the Tukey jackknife variance estimator is not unbiased for the variance of regression coefficients (Hinkley 1977). The bias depends on the X matrix. For ordinary least squares regression (OLSR), the bias can be calculated, and depends on the number of observations n and the number of parameters k in the model. For the common case of an orthogonal design matrix with ± 1 levels, the delete-one jackknife estimate equals $(n - 1)/(n - k)$ times the classical variance estimate for the regression coefficients in OLSR. Similar expressions hold for delete-d estimates. Modifications have been proposed to reduce or eliminate the bias for the OLSR case, however, they depend on the number of parameters used in the model. See e.g. Hinkley (1977) or Wu (1986).

Thus, the results of `var.jack` should be used with caution.

Author(s)

Bjørn-Helge Mevik

References

Tukey J.W. (1958) Bias and Confidence in Not-quite Large Samples. (Abstract of Preliminary Report). *Annals of Mathematical Statistics*, **29**(2), 614.

Martens H. and Martens M. (2000) Modified Jack-knife Estimation of Parameter Uncertainty in Bilinear Modelling by Partial Least Squares Regression (PLSR). *Food Quality and Preference*, **11**, 5–16.

Hinkley D.V. (1977), Jackknifing in Unbalanced Situations. *Technometrics*, **19**(3), 285–292.

Wu C.F.J. (1986) Jackknife, Bootstrap and Other Resampling Methods in Regression Analysis. *The Annals of Statistics*, **14**(4), 1261–1295.

See Also

[mvrCv](#), [jack.test](#)

Examples

```
data(oliveoil)
mod <- pcr(sensory ~ chemical, data = oliveoil, validation = "LOO",
          jackknife = TRUE)
var.jack(mod, ncomp = 2)
```

widekernelpls.fit	NA
-------------------	----

Description

Fits a PLSR model with the wide kernel algorithm.

Usage

```
widekernelpls.fit(X, Y, ncomp, stripped = FALSE,
                 tol = .Machine$double.eps^0.5, maxit = 100, ...)
```

Arguments

X	a matrix of observations. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
stripped	logical. If TRUE the calculations are stripped as much as possible for speed; this is meant for use with cross-validation or simulations when only the coefficients are needed. Defaults to FALSE.
tol	numeric. The tolerance used for determining convergence in the algorithm.
maxit	positive integer. The maximal number of iterations used in the internal Eigen-vector calculation.
...	other arguments. Currently ignored.

Details

This function should not be called directly, but through the generic functions `plsr` or `mvr` with the argument `method="widekernelpls"`. The wide kernel PLS algorithm is efficient when the number of variables is (much) larger than the number of observations. For very wide X, for instance 12x18000, it can be twice as fast as `kernelpls.fit` and `simpls.fit`. For other matrices, however, it can be much slower. The results are equal to the results of the NIPALS algorithm.

Value

A list containing the following components is returned:

coefficients	an array of regression coefficients for 1, ..., ncomp components. The dimensions of coefficients are <code>c(nvar, npred, ncomp)</code> with <code>nvar</code> the number of X variables and <code>npred</code> the number of variables to be predicted in Y.
scores	a matrix of scores.
loadings	a matrix of loadings.
loading.weights	a matrix of loading weights.
Yscores	a matrix of Y-scores.
Yloadings	a matrix of Y-loadings.
projection	the projection matrix used to convert X to scores.
Xmeans	a vector of means of the X variables.
Ymeans	a vector of means of the Y variables.
fitted.values	an array of fitted values. The dimensions of <code>fitted.values</code> are <code>c(nobj, npred, ncomp)</code> with <code>nobj</code> the number samples and <code>npred</code> the number of Y variables.
residuals	an array of regression residuals. It has the same dimensions as <code>fitted.values</code> .

Xvar a vector with the amount of X-variance explained by each number of components.
Xtotvar Total variance in X.

If `stripped` is TRUE, only the components coefficients, `Xmeans` and `Ymeans` are returned.

Note

The current implementation has not undergone extensive testing yet, and should perhaps be regarded as experimental. Specifically, the internal Eigenvector calculation does not always converge in extreme cases where the Eigenvalue is close to zero. However, when it does converge, it always converges to the same results as `kernelpls.fit`, up to numerical inaccuracies.

The algorithm also has a bit of overhead, so when the number of observations is moderately high, `kernelpls.fit` can be faster even if the number of predictors is much higher. The relative speed of the algorithms can also depend greatly on which BLAS and/or LAPACK library R is linked against.

Author(s)

Bjørn-Helge Mevik

References

Rännar, S., Lindgren, F., Geladi, P. and Wold, S. (1994) A PLS Kernel Algorithm for Data Sets with Many Variables and Fewer Objects. Part 1: Theory and Algorithm. *Journal of Chemometrics*, **8**, 111–125.

See Also

[mvr](#) [pls](#) [cppls](#) [pcr](#) [kernelpls.fit](#) [simpls.fit](#) [oscorespls.fit](#)

yarn

NIR spectra and density measurements of PET yarns

Description

A training set consisting of 21 NIR spectra of PET yarns, measured at 268 wavelengths, and 21 corresponding densities. A test set of 7 samples is also provided. Many thanks to Erik Swierenga.

Usage

yarn

Format

A data frame with components

NIR Numeric matrix of NIR measurements

density Numeric vector of densities

train Logical vector with TRUE for the training samples and FALSE for the test samples

Source

Swierenga H., de Weijer A. P., van Wijk R. J., Buydens L. M. C. (1999) Strategy for constructing robust multivariate calibration models *Chemometrics and Intelligent Laboratory Systems*, **49**(1), 1–17.

Index

*Topic **classification**

cppls.fit, 8

*Topic **datasets**

gasoline, 14

mayonnaise, 18

oliveoil, 28

yarn, 52

*Topic **hplot**

biplot.mvr, 2

coefplot, 6

plot.mvr, 30

predplot, 34

scoreplot, 36

validationplot, 46

*Topic **htest**

jack.test, 15

*Topic **models**

cvsegments, 13

*Topic **multivariate**

biplot.mvr, 2

coef.mvr, 4

coefplot, 6

cppls.fit, 8

crossval, 11

kernelpls.fit, 17

msc, 19

mvr, 20

mvrCv, 23

mvrVal, 25

oscorespls.fit, 28

plot.mvr, 30

pls.options, 31

predict.mvr, 33

predplot, 34

scoreplot, 36

scores, 40

simpls.fit, 41

stdize, 43

summary.mvr, 44

svdpc.fit, 45

validationplot, 46

widekernelpls.fit, 50

*Topic **regression**

biplot.mvr, 2

coef.mvr, 4

coefplot, 6

cppls.fit, 8

crossval, 11

kernelpls.fit, 17

msc, 19

mvr, 20

mvrCv, 23

mvrVal, 25

oscorespls.fit, 28

plot.mvr, 30

pls.options, 31

predict.mvr, 33

predplot, 34

scoreplot, 36

scores, 40

simpls.fit, 41

stdize, 43

summary.mvr, 44

svdpc.fit, 45

validationplot, 46

widekernelpls.fit, 50

*Topic **univar**

var.jack, 49

biplot.default, 3

biplot.mvr, 2, 30

coef, 4, 5

coef.mvr, 4, 6, 8, 22, 34, 41

coefplot, 6, 30

compnames (coef.mvr), 4

corrplot, 30

corrplot (scoreplot), 36

cppls, 18, 32, 46, 52

- cppls (mvr), 20
- cppls.fit, 8, 22
- crossval, 11, 22, 24, 25, 27
- cvsegments, 12, 13, 13, 24, 25
- explvar, 40
- explvar (coef.mvr), 4
- fitted, 4, 5
- fitted.mvr (coef.mvr), 4
- gasoline, 14
- identify, 38, 39
- jack.test, 12, 13, 15, 24, 25, 50
- kernelpls.fit, 17, 22, 30, 42, 51, 52
- legend, 8, 39, 48
- lm, 21
- loading.weights, 22
- loading.weights (scores), 40
- loadingplot, 30
- loadingplot (scoreplot), 36
- loadings, 5, 22, 38–40
- loadings (scores), 40
- locator, 7, 38, 47
- makepredictcall, 19, 43
- makepredictcall.msc (msc), 19
- makepredictcall.stdized (stdize), 43
- matplot, 48
- mayonnaise, 18
- model.frame, 5
- model.frame.mvr (coef.mvr), 4
- model.matrix, 5
- model.matrix.mvr (coef.mvr), 4
- msc, 19, 44
- MSEP, 13, 22, 25, 45, 47, 48
- MSEP (mvrVal), 25
- mvr, 3, 5, 8, 10, 13, 18, 20, 20, 25, 27, 30, 31, 34, 36, 39, 41, 42, 44–46, 48, 52
- mvrCv, 13, 16, 21, 22, 23, 27, 31, 50
- mvrVal, 25
- mvrValstats (mvrVal), 25
- na.exclude, 21
- na.fail, 21
- na.omit, 5, 21, 33
- oliveoil, 28
- options, 5, 21
- oscorespls.fit, 10, 18, 22, 28, 42, 52
- par, 7, 35, 37, 47, 48
- pcr, 10, 18, 20, 30, 32, 42, 44–46, 52
- pcr (mvr), 20
- plot, 6, 8, 35, 37, 47
- plot.loadings (scoreplot), 36
- plot.mvr, 3, 8, 22, 30, 34, 36, 38, 39, 48
- plot.mvrVal, 27
- plot.mvrVal (validationplot), 46
- plot.scores (scoreplot), 36
- pls.options, 31
- plsr, 10, 18, 20, 30, 32, 42, 44–46, 52
- plsr (mvr), 20
- points, 7, 37, 47
- predict.msc (msc), 19
- predict.mvr, 21, 22, 33
- predict.stdized (stdize), 43
- prednames (coef.mvr), 4
- predplot, 33, 34
- predplot.mvr, 30
- predplotXy (predplot), 34
- print.jacktest (jack.test), 15
- print.mvr (summary.mvr), 44
- print.mvrVal (summary.mvr), 44
- printCoefmat, 15
- R2, 22, 33, 47, 48
- R2 (mvrVal), 25
- residuals, 4, 5
- residuals.mvr (coef.mvr), 4
- respnames (coef.mvr), 4
- RMSEP, 22, 33, 45, 47, 48
- RMSEP (mvrVal), 25
- scale, 43, 44
- scoreplot, 30, 36
- scores, 5, 22, 38, 39, 40
- simpls.fit, 10, 18, 22, 30, 41, 51, 52
- sm.options, 32
- stdize, 20, 43
- summary.mvr, 34, 44
- svdpc.fit, 22, 45
- title, 7, 35, 38, 47
- validationplot, 27, 30, 46

`var.jack`, [12](#), [13](#), [15](#), [16](#), [24](#), [25](#), [49](#)

`widekernelpls.fit`, [10](#), [18](#), [22](#), [30](#), [42](#), [50](#)

`yarn`, [52](#)

`Yloadings`, [5](#)

`Yloadings (scores)`, [40](#)

`Yscores (scores)`, [40](#)