

Package ‘smacof’

January 2, 2012

Type Package

Title SMACOF for Multidimensional Scaling.

Version 1.2-1

Date 2011-11-30

Author Jan de Leeuw, Patrick Mair

Maintainer Jan de Leeuw <deleeuw@stat.ucla.edu>

Description This package provides the following approaches of multidimensional scaling (MDS) based on stress minimization by means of majorization (smacof): Simple smacof on symmetric dissimilarity matrices, smacof for rectangular matrices (unfolding models), smacof with constraints on the configuration, three-way smacof for individual differences (including constraints for idioscal, indscal, and identity), and spherical smacof (primal and dual algorithm). Each of these approaches is implemented in a metric and non-metric manner including primary, secondary, and tertiary approaches for tie handling. Jack-knife and permutation tests are included as well.

Imports graphics, stats

Depends R (>= 2.13.0), polynom, rgl, scatterplot3d, Hmisc, colorspace

License GPL-2

Repository CRAN

Date/Publication 2011-11-29 16:49:27

R topics documented:

smacof-package	2
bread	3
breakfast	4
csrranking	5
ekman	5
EW_ger	6

helm	7
jackknife	8
kinshipdelta	10
partypref	10
perception	11
permtest	12
plot.smacof	13
plot3d.smacof	15
rectangles	17
residuals.smacof	18
sim2diss	18
smacofConstraint	19
smacofIndDiff	21
smacofRect	24
smacofSphere.dual	25
smacofSym	27
stardist	29
summary.smacofB	29
trading	30
winedat	32
wish_ger	32

Index 34

smacof-package	<i>SMACOF for Multidimensional Scaling.</i>
----------------	---

Description

This package provides the following approaches of multidimensional scaling (MDS) based on stress minimization by means of majorization (smacof): Simple smacof on symmetric dissimilarity matrices, smacof for rectangular matrices (unfolding models), smacof with constraints on the configuration, three-way smacof for individual differences (including constraints for idioscal, indscal, and identity), and spherical smacof (primal and dual algorithm). Each of these approaches is implemented in a metric and nonmetric manner including primary, secondary, and tertiary approaches for tie handling.

Details

Package:	smacof
Type:	Package
Version:	1.0-0
Date:	2008-07-31
License:	GPL

The function for basic SMACOF on symmetric dissimilarity matrices is `smacofSym()`. For rectangular input matrices (unfolding model) `smacofRect()` is appropriate and by means of `smacofIndDiff()` individual difference models (three-way MDS) can be computed.

Author(s)

Jan de Leeuw, Patrick Mair

Maintainer: Jan de Leeuw <deleeuw@stat.ucla.edu>

References

de Leeuw, J. & Mair, P. (2009). Multidimensional scaling using majorization: The R package `smacof`. *Journal of Statistical Software*, 31(3), 1-30, <http://www.jstatsoft.org/v31/i03/>

See Also

[smacofSym](#), [smacofRect](#), [smacof](#), [smacofIndDiff](#), [smacofSphere.primal](#), [smacofSphere.dual](#)

Examples

```
data(trading)
res <- smacofSym(trading)
res
```

bread

Breakfast preferences

Description

The data set is described in Bro (1998). The raw data consist of ratings of 10 breads on 11 different attributes carried out by 8 raters. Note that the bread samples are pairwise replications: Each of the 5 different breads, which have a different salt content, was presented twice for rating.

Usage

```
data(bread)
```

Format

A list of length 8 with elements of class "dist". The attributes are bread odor, yeast odor, off-flavor, color, moisture, dough, salt taste, sweet taste, yeast taste, other taste, and total taste.

References

Bro, R. (1998). *Multi-way Analysis in the Food Industry: Models, Algorithms, and Applications*. Ph.D. thesis, University of Amsterdam (NL) & Royal Veterinary and Agricultural University (DK).

Examples

```
data(bread)
```

```
breakfast
```

```
Breakfast preferences
```

Description

42 individuals were asked to order 15 breakfast items due to their preference.

Usage

```
data(breakfast)
```

Format

Data frame with students in the rows and breakfast items in the columns.

toast: toast pop-up

butoast: buttered toast

engmuff: English muffin and margarine

jdonut: jelly donut

cintoast: cinnamon toast

bluemuff: blueberry muffin and margarine

hrolls: hard rolls and butter

toastmarm: toast and marmalade

butoastj: buttered toast and jelly

toastmarg: toast and margarine

cinbun: cinnamon bun

danpastry: Danish pastry

gdonut: glazed donut

cofcake: coffee cake

cornmuff: corn muffin and butter

References

Green, P. E. & Rao, V. (1972). Applied multidimensional scaling. Hinsdale, IL: Dryden.

Examples

```
data(breakfast)
```

csrranking

CSR activities

Description

This dataset collects rankings of 100 individual on 5 topics that reflect social responsibilities on corporations.

Usage

```
data(csrranking)
```

Format

A data frame where each individual ranked prevention of environmental pollution (Environment), waste prevention (Waste Prevention), selling organic products (Organic Products), participating on charity programs (Charity), and fair treatment of employees (Employee) according to its own preferences. A value of 1 corresponds to highest importance, 5 to lowest importance.

Examples

```
data(csrranking)
```

ekman

Ekman data set

Description

Ekman dissimilarities

Usage

```
data(ekman)
```

Format

Object of class `dist`

Details

Ekman presents similarities for 14 colors which are based on a rating by 31 subjects where each pair of colors was rated on a 5-point scale (0 = no similarity up to 4 = identical). After averaging, the similarities were divided by 4 such that they are within the unit interval. Similarities of colors with wavelengths from 434 to 674 nm.

References

Ekman, G. (1954). Dimensions of color vision. *Journal of Psychology*, 38, 467-474.

Examples

```
data(ekman)
## maybe str(ekman) ; plot(ekman) ...
```

EW_ger

Work values

Description

Intercorrelations of 13 working values for former West (first list element) and East Germany.

Usage

```
data(EW_eng)
```

Format

Object of class `dist`

Details

Note that in `EW_ger` the labels are given in German. For `smacof`, the data must be converted into a dissimilarity matrix by applying the `sim2diss()` function to each list element.

References

ALLBUS 1991, German General Social Survey.

Borg, I., Groenen, P. J. F., & Mair, P. (2010). *Multidimensionale Skalierung*. Muenchen: Hampp Verlag.

Borg, I., Groenen, P. J. F., & Mair, P. (2012). *Multidimensional Scaling*. New York: Springer, forthcoming.

Examples

```
data(EW_eng)
data(EW_ger)
```

`helm`*Helm's color data*

Description

This dataset contains dissimilarity data for individual difference scaling from an experiment carried out by Helm (1959).

Usage

```
data(helm)
```

Format

List containing objects of class `dist`

Details

A throughout description of the experiment can be found in Borg and Groenen (2005, p. 451) with the corresponding Table 21.1. containing distance estimates for color pairs. There were 14 subjects that rated the similarity of colors, 2 of whom replicated the experiment. 10 subjects have a normal color vision (labelled by N1 to N10 in our list object), 4 of them are red-green deficient in varying degrees. In this dataset we give the dissimilarity matrices for each of the subjects, including the replications. They are organized as a list of length 16 suited for `smacofIndDiff` computations.

The authors thank Michael Friendly and Phil Spector for data preparation.

References

Helm, C. E. (1959). A multidimensional ratio scaling analysis of color relations. Technical Report, Princeton University and Educational Testing Service. Princeton, NJ.

Borg, I., & Groenen, P. J. F. (2005). Modern Multidimensional Scaling: Theory and Applications (2nd edition). New York: Springer.

Examples

```
data(helm)
length(helm)
helm
```

 jackknife

SMACOF Jackknife

Description

These methods perform a SMACOF Jackknife and plot the corresponding solution.

Usage

```
## S3 method for class 'smacofB'
jackknife(object, eps = 1e-6, itmax = 100, verbose = FALSE)
```

```
## S3 method for class 'smacofJK'
plot(x, plot.dim = c(1,2), hclpar = list(start = 30, end = 200), plot.lines = TRUE, main, xlab, ylab, xlim, ylim)
```

Arguments

object	Object of class "smacofB", i.e., an MDS solution from <code>smacofSym()</code>
itmax	Maximum number of iterations
eps	Convergence criterion
verbose	If TRUE, intermediate stress is printed out
x	Object of class "smacofJK"
plot.dim	Vector with dimensions to be plotted.
hclpar	Parameters to be used for HCL colors (further details see rainbow_hcl)
plot.lines	If TRUE, the Jackknife configurations are plotted and connected with their centroid
main	Plot title.
xlab	Label of x-axis.
ylab	Label of y-axis.
xlim	Scale x-axis.
ylim	Scale y-axis.
...	Further plot arguments passed: see plot for detailed information.

Details

In order to examine the stability solution of an MDS, a Jackknife on the configurations can be performed (see de Leeuw & Meulman, 1986) and plotted. The plot shows the jackknife configurations which are connected to their centroid. In addition, the original smacof configuration (transformed through Procrustes) is plotted. The Jackknife function itself returns also a stability measure (as ratio of between and total variance), a measure for cross validity, and the dispersion around the original smacof solution.

Value

smacof.conf	SMACOF configurations
jackknife.conf	An array of n-1 configuration matrices for each Jackknife MDS solution
comparison.conf	Centroid Jackknife configurations (comparison matrix)
stab	Stability measure
cross	Cross validity
disp	Dispersion
loss	Value of the loss function
ndim	Number of dimensions
call	Model call
niter	Number of iterations
nobj	Number of objects

Author(s)

Jan de Leeuw and Patrick Mair

References

De Leeuw, J., & Meulman, J. (1986). A special jackknife for multidimensional scaling. *Journal of Classification*, 3, 97-112.

See Also

[smacofSym](#), [smacofConstraint](#), [plot.smacof](#)

Examples

```
## symmetric smacof
data(kinshipdelta)
res.smacof <- smacofSym(kinshipdelta)
res.jk <- jackknife(res.smacof)
res.jk

plot(res.jk)
plot(res.jk, hclpar = list(10, 500))
plot(res.jk, hclpar = list(10, 300), plot.lines = FALSE)
```

kinshipdelta

Kinship Terms

Description

Percentages of how often 15 kinship terms were not grouped together by college students including three external scales.

Usage

```
data(kinshipdelta)
```

```
data(kinshipscales)
```

Format

Dissimilarity matrix of 15 kinship terms and data frame with the following external scales:

Gender (1 = male, 2 = female, 9 = missing)

Generation (-2 = two back, -1 = one back, 0 = same generation, 1 = one ahead, 2 = two ahead)

Degree (1 = first, 2 = second, 3 = third, 4 = fourth)

References

Rosenberg, S. & Kim, M. P. (1975). The method of sorting as a data gathering procedure in multivariate research. *Multivariate Behavioral Research*, 10, 489-502.

Examples

```
data(kinshipdelta)  
data(kinshipscales)
```

partypref

Party preferences

Description

Artificial dataset containing the judges in the rows and the parties in the columns.

Usage

```
data(partypref)
```

Format

Matrix of party preferences.

References

Borg, I., Groenen, P. J. F., & Mair, P. (2010). *Multidimensionale Skalierung*. Muenchen: Hampp Verlag.

Examples

```
data(partypref)
```

perception

Rectangle Perception Data

Description

42 subjects are assigned to two groups of 21 persons. 120 stimulus pairs of rectangles are presented. One group judges on a scale from 0 to 9 the perception in terms of width-height (WH), the other group in terms of size-shape (SS).

Usage

```
data(perception)
```

Format

List of subject dissimilarities for WH and SS group.

References

Borg, I. & Leutner, D. (1983). Dimensional models for the perception of rectangles. *Perception and Psychophysics*, 34, 257-269.

Examples

```
data(perception)
```

 permtest

SMACOF Jackknife

Description

These methods perform a permutation test for a nonmetric symmetric SMACOF solution.

Usage

```
## S3 method for class 'smacofB'
permtest(object, nrep = 100, verbose = FALSE)
```

```
## S3 method for class 'smacofPerm'
plot(x, alpha = 0.05, main, xlab, ylab, ...)
```

Arguments

object	Object of class "smacofB", i.e., an MDS solution from smacofSym()
nrep	Number of permutations
verbose	If TRUE, intermediate stress is printed out
x	Object of class "smacofPerm"
alpha	Alpha level
main	Plot title.
xlab	Label of x-axis.
ylab	Label of y-axis.
...	Further plot arguments passed: see plot for detailed information.

Details

This routine permutes m dissimilarity values, where m is the number of lower diagonal elements in the corresponding dissimilarity matrix. For each sample a symmetric, nonmetric SMACOF of dimension $ndim$ is computed and the stress values are stored in `stressvec`. Using the fitted stress value, the p-value is computed. Subsequently, the empirical cumulative distribution function can be plotted using the `plot` method.

Value

<code>stressvec</code>	Vector containing the stress values of the permutation samples
<code>stress.nm</code>	Fitted nonmetric stress
<code>pval</code>	Resulting P-values
<code>call</code>	Model call
<code>nrep</code>	Number of permutations
<code>nobj</code>	Number of objects

Author(s)

Jan de Leeuw and Patrick Mair

References

De Leeuw, J., & Stoop, I. (1984). Upper bounds for Kruskal's stress. *Psychometrika*, 49, 301-402.

See Also

[jackknife.smacofB](#), [smacofSym](#), [plot.smacof](#)

Examples

```
## symmetric smacof
data(kinshipdelta)
res.smacof <- smacofSym(kinshipdelta, ndim = 1, metric = FALSE)
res.perm <- permtest(res.smacof, verbose = TRUE)
res.perm

plot(res.perm)
```

plot.smacof

2D SMACOF plots

Description

These methods provide various 2D plots for SMACOF models.

Usage

```
## S3 method for class 'smacof'
plot(x, plot.type = "confplot", plot.dim = c(1,2), sphere = TRUE, bubscale = 3, label.conf = list(label = TRUE, pos = 1, size = 10))

## S3 method for class 'smacofR'
plot(x, plot.type = "confplot", joint = FALSE, plot.dim = c(1,2), col.rows = "red", col.columns = "blue", label.conf = list(label = TRUE, pos = 1, size = 10))

## S3 method for class 'smacofID'
plot(x, plot.type = "confplot", plot.dim = c(1,2), bubscale = 5, label.conf = list(label = TRUE, pos = 1, size = 10))
```

Arguments

x	Object of class "smacof", "smacofR", and "smacofID" (see details)
plot.type	String indicating which type of plot to be produced: "confplot", "resplot", "Shepard", "stressplot" (see details)
plot.dim	Vector with dimensions to be plotted.

main	Plot title.
xlab	Label of x-axis.
ylab	Label of y-axis.
xlim	Scale x-axis.
ylim	Scale y-axis.
type	What type of plot should be drawn (see also plot).
sphere	In case of spherical smacof, whether sphere should be plotted or not.
bubscale	Scaling factor (size) for the bubble plot.
label.conf	List with arguments for plotting the labels of the configurations in a configuration plot (logical value whether to plot labels or not, label position, label color).
identify	If TRUE, the <code>identify()</code> function is called internally that allows to add configuration labels by mouse click.
joint	If TRUE, the configurations are plotted jointly in rectangular smacof.
col.rows	Row colors in rectangular configuration plot.
col.columns	Column colors in rectangular configuration plot.
label.conf.rows	List with arguments for plotting the labels of the row configurations in a rectangular configuration plot (logical value whether to plot labels or not, label position, label color).
label.conf.columns	List with arguments for plotting the labels of the columns configurations in a rectangular configuration plot (logical value whether to plot labels or not, label position, label color).
...	Further plot arguments passed: see plot for detailed information.

Details

`smacofSym()` creates object of class "smacof", whereas `smacofRect()` produces "smacofR" and `smacofIndDiff()` generates "smacofID".

Plot description:

- Configuration plot (`plot.type = "confplot"`): Plots the MDS configurations.
- Residual plot (`plot.type = "resplot"`): Plots the normalized dissimilarities (d-hats) distances against the fitted distances.
- Shepard diagram (`plot.type = "Shepard"`): Diagram with the observed dissimilarities against the fitted distances including (isotonic) regression line.
- Stress decomposition plot (`plot.type = "stressplot"`): Plots the stress contribution in of each observation. The higher the contribution, the worse the fit.
- Bubble plot (`plot.type = "bubbleplot"`, not available for rectangular SMACOF): Combines the configuration plot with the point stress contribution. The larger the bubbles, the better the fit.

For `smacofIndDiff()` the residual plot, Shepard diagram, and stress plot are based on the sum of the residuals across individuals/ways. The configuration plot represents the group stimulus space (i.e., joint configurations).

See Also[plot3d.smacof](#)**Examples**

```
## 2D plots for spherical SMACOF
data(trading)
res <- smacofSym(trading)
plot(res, plot.type = "confplot")
plot(res, plot.type = "Shepard")
plot(res, plot.type = "stressplot")
plot(res, plot.type = "resplot")
plot(res, plot.type = "bubbleplot")
```

```
## Joint configuration plot and row/column stressplots for rectangular SMACOF
data(breakfast)
res <- smacofRect(breakfast)
plot(res, plot.type = "confplot", joint = TRUE)
plot(res, plot.type = "stressplot")
plot(res, type = "p", pch = 25)
plot(res, type = "p", pch = 25, col.columns = 3, label.conf.columns = list(label = TRUE, pos = 3, col = 3), col.rows = 3)
plot(res, joint = TRUE, type = "p", pch = 25, col.columns = 4, label.conf.columns = list(label = TRUE, pos = 3, col = 3))
```

plot3d.smacof

3D SMACOF plots

Description

These methods produce static and dynamic 3D configuration plots for SMACOF models.

Usage

```
## S3 method for class 'smacof'
plot3d(x, plot.dim = c(1,2,3), sphere = FALSE, xlab, ylab, zlab,
col, main, bgpng = NULL, ax.grid = TRUE, sphere.rgl = FALSE,...)
```

```
## S3 method for class 'smacofR'
plot3d(x, plot.dim = c(1,2,3), joint = FALSE, xlab, ylab, zlab,
col, main, bgpng = NULL, ax.grid = TRUE, sphere.rgl = FALSE,...)
```

```
## S3 method for class 'smacofID'
plot3d(x, plot.dim = c(1,2,3), xlab, ylab, zlab,
col, main, bgpng = NULL, ax.grid = TRUE, sphere.rgl = FALSE,...)
```

```
## S3 method for class 'smacof'
plot3dstatic(x, plot.dim = c(1,2,3), main, xlab, ylab, zlab, col, ...)
```

```
## S3 method for class 'smacofR'
plot3dstatic(x, plot.dim = c(1,2,3), main, xlab, ylab, zlab, col, joint = FALSE, ...)

## S3 method for class 'smacofID'
plot3dstatic(x, plot.dim = c(1,2,3), main, xlab, ylab, zlab, col, ...)
```

Arguments

x	Object of class "smacof", "smacofR", and "smacofID" (see details)
plot.dim	Vector of length 3 with dimensions to be plotted.
sphere	Spherical SMACOF: Whether sphere should be plotted or not.
joint	Rectangular SMACOF: If TRUE, the configurations are plotted jointly.
main	Plot title.
xlab	Label of x-axis.
ylab	Label of y-axis.
zlab	Label of z-axis.
col	Color of the text labels.
bgpng	Background image from rgl library; NULL for white background
ax.grid	If TRUE, axes grid is plotted.
sphere.rgl	If TRUE, rgl sphere (background) is plotted.
...	Further plot arguments passed: see plotin package scatterplot3d for detailed information.

Details

smacofSym() creates object of class "smacof", whereas smacofRect() produces "smacofR" and smacofIndDiff() generates "smacofID".

For smacofIndDiff() the configuration plot represents the group stimulus space (i.e., joint configurations).

See Also

[plot.smacof](#)

Examples

```
## 3D plot for spherical SMACOF
data(trading)
res <- smacofSphere.dual(trading, ndim = 3)
plot3d(res, plot.type = "confplot", sphere = TRUE, sphere.rgl = FALSE)
plot3dstatic(res)

## Group stimulus space for rectangular SMACOF
```

```
data(breakfast)
res <- smacofRect(breakfast, ndim = 3)
plot3d(res, joint = TRUE)
```

rectangles

Rectangles

Description

These data are based on an experiment by Borg and Leutner (1983). They constructed rectangles based on a specific grid structure. The size of the rectangles is given in the constraints matrix. In total, we have 16 rectangles. 21 subjects had to rate twice the similarity of each pair of rectangles on a scale from 0 (identical) to 9 (very different). The dist object contains the average ratings which are dissimilarities.

Usage

```
data(rectangles)
data(rect_constr)
```

Format

The rectangles are object of class `dist`, the constraints are given as matrix

Details

Note that the labels are given in German.

References

Borg, I., & Leutner, D. (1983). Dimensional models for the perception of rectangles. *Perception and Psychophysics*, 34, 257-269.

Borg, I., Groenen, P. J. F., & Mair, P. (2010). *Multidimensionale Skalierung*. Muenchen: Hampp Verlag.

Examples

```
data(rectangles)
data(rect_constr)
```

residuals.smacof	<i>Residuals</i>
------------------	------------------

Description

Computes the residuals by subtracting the configuration dissimilarities from the observed dissimilarities.

Usage

```
## S3 method for class 'smacof'
residuals(object, ...)
## S3 method for class 'smacofR'
residuals(object, ...)
## S3 method for class 'smacofID'
residuals(object, ...)
```

Arguments

object	Object of class smacof, smacofR (rectangular), or smacofID (individual differences)
...	Ignored

Examples

```
data(kinshipdelta)
res <- smacofSym(kinshipdelta)
residuals(res)
```

sim2diss	<i>Converts similarities to dissimilarities</i>
----------	---

Description

Utility function for converting similarities into dissimilarities. Different methods are provided.

Usage

```
sim2diss(similmat, method = "corr", to.dist = TRUE)
```

Arguments

similmat	Similarity matrix (not necessarily symmetric, nor quadratic)
method	Various methods for converting similarities into dissimilarities: "corr", "neglog", "counts", or an integer value (see details)
to.dist	If TRUE, object of class dist is produced

Details

We provide the following methods for converting similarities S into dissimilarities D : "corr" is suited for correlation matrices and takes $D = \sqrt{1-S}$. "neglog" takes the negative logarithm in terms of $-\log(S)$. Having frequencies, "counts" is appropriate which does $-\log((S[i,j]*S[j,i])/(S[i,i]*S[j,j]))$. The user can specify also an integer value v . In this case `sim2diss()` computes $v-S$.

Value

Returns dissimilarities either as matrix or as dist object.

Examples

```
## Converting Ekman data (similarities) into dissimilarities by subtraction from 1
data(ekman)
ekman.diss <- sim2diss(ekman, method = 1)
res <- smacofSym(ekman.diss)
```

smacofConstraint *SMACOF Constraint*

Description

SMACOF with constraints on the configurations.

Usage

```
smacofConstraint(delta, constraint = "linear", external, ndim = 2, weightmat = NULL, init = NULL,
metric = TRUE, ties = "primary", verbose = FALSE, modulus = 1, itmax = 1000, eps = 1e-6)
```

Arguments

delta	Either a symmetric dissimilarity matrix or an object of class "dist"
constraint	Type of constraint: "linear", "unique", "diagonal", or a user-specified function (see details)
external	Data frame or matrix with external covariates, or list for simplex and circumplex (see details)
ndim	Number of dimensions
weightmat	Optional matrix with dissimilarity weights
init	Optional matrix with starting values for configurations
metric	If FALSE non-metric MDS is performed
ties	Tie specification for non-metric MDS only: "primary", "secondary", or "tertiary"
verbose	If TRUE, intermediate stress is printed out
modulus	Number of smacof iterations per monotone regression call
itmax	Maximum number of iterations
eps	Convergence criterion

Details

The argument `external` is mandatory and allows for the specification of a covariate data frame (or matrix) of dimension $(n \times q)$. Alternatively, for simplex fitting the user can specify a list of the following structure: `external = list("simplex", dim2)` with `dim2` denoting the dimension of the simplex with $\text{dim2} < n$. For a circumplex fitting, the list has to be of the following form: `external = list("circumplex", dim2, k1, k2)` with $1 \leq k1 \leq k2 \leq n$ (see also examples section). `k1` and `k2` denote the circumplex width.

In constraint `smacof`, the configuration matrix is subject of a constraint based on the external scales (predictors). This constraint can be specified using the `constraint` argument. We provide the following standard setting:

For `constraint = "linear"` the configurations X are decomposed linearly, i.e. $X = ZC$ where Z is the known predictor matrix specified using `external`.

The same for `constraint = "diagonal"` where X needs to be of dimension $(n \times q)$ where q is the number of columns of the external scale matrix (and thus number of dimensions). Here, C is restricted to be diagonal.

For `constraint = "unique"` we get the Bentler-Weeks uniqueness model. Hence X is of dimension $(n \times (n + p))$. This implies that we fit a certain number of dimensions p and, in addition we extract n additional dimensions where each object is scored on a separate dimension. More technical details can be found in the corresponding JSS article (reference see below).

In addition, the user can specify his own constraint function with the following arguments: configuration matrix with starting values (`init`) (mandatory in this case), matrix V (`weightmat`; based on the weight matrix, see package `vignette`), external scale matrix (`external`). The function must return a matrix of resulting configurations.

Value

<code>delta</code>	Observed dissimilarities
<code>obsdiss</code>	Observed dissimilarities, normalized
<code>confdiss</code>	Configuration dissimilarities
<code>conf</code>	Matrix of final configurations
<code>stress.m</code>	stress value for metric MDS
<code>stress.nm</code>	stress value for non-metric MDS (if computed)
<code>spp</code>	Stress per point
<code>ndim</code>	Number of dimensions
<code>model</code>	Type of <code>smacof</code> model
<code>niter</code>	Number of iterations
<code>nobj</code>	Number of objects

Author(s)

Jan de Leeuw and Patrick Mair

References

- de Leeuw, J. & Mair, P. (2009). Multidimensional scaling using majorization: The R package smacof. *Journal of Statistical Software*, 31(3), 1-30, <http://www.jstatsoft.org/v31/i03/>
- de Leeuw, J., & Heiser, W. (1980). Multidimensional scaling with restrictions on the configurations. In P. R. Krishnaiah (eds.), *Multivariate Analysis V*, pp. 501-522. North-Holland.

See Also

[smacofSym](#), [smacofRect](#), [smacofIndDiff](#), [smacofSphere.primal](#), [smacofSphere.dual](#)

Examples

```
## SMACOF with linear configuration constraints
data(kinshipdelta)
data(kinshipscales)
res.lin1 <- smacofConstraint(kinshipdelta, constraint = "linear", external = kinshipscales)

## X = ZC decomposition
Z <- as.matrix(kinshipscales)      ## matrix Z with external constraints
X <- res.lin1$conf                 ## resulting configurations X
C <- solve(t(Z)%*%Z)%*%t(Z)%*%X   ## compute C out of X = ZC
C
Z

## SMACOF with diagonal constraints
res.diag <- smacofConstraint(kinshipdelta, constraint = "diagonal", external = kinshipscales, ndim = 3)
X <- res.diag$conf                 ## resulting configurations X
C <- solve(t(Z)%*%Z)%*%t(Z)%*%X   ## compute C out of X = ZC
round(C, 3)
Z%*%C                             ## check: should be equal to X

## SMACOF with unique constraints (Bentler-Weeks model)
res.unique <- smacofConstraint(kinshipdelta, constraint = "unique", external = kinshipscales)

## Fitting a simplex with q = 4 (i.e., n-1), diagonal constraints
res.simp <- smacofConstraint(kinshipdelta, constraint = "diagonal", external = list("simplex", 4), ndim = 3)
plot3d(res.simp)

## Fitting a circumplex with q = 3, k1 = 1, k2 = 2, diagonal constraints
res.circ <- smacofConstraint(kinshipdelta, constraint = "diagonal", external = list("circumplex", 3, 1, 2), ndim = 3)
plot3d(res.circ)
```

Description

Performs smacof for individual differences also known as Three-Way smacof on a list of dissimilarity matrices. Various restrictions decompositions and restrictions on the weight matrix are provided.

Usage

```
smacofIndDiff(delta, ndim = 2, weightmat = NULL, init = NULL, metric = TRUE,
              ties = "primary", constraint = "indscale", verbose = FALSE, modulus = 1,
              itmax = 1000, eps = 1e-6)
```

Arguments

delta	A list of dissimilarity matrices or a list objects of class dist
ndim	Number of dimensions
weightmat	Optional matrix with dissimilarity weights
init	Matrix with starting values for configurations (optional)
metric	If FALSE non-metric MDS is performed
ties	Tie specification for non-metric MDS
constraint	Either "indscale", "idioscale", or "identity" (see details)
verbose	If TRUE, intermediate stress is printed out
modulus	Number of smacof iterations per monotone regression call
itmax	Maximum number of iterations
eps	Convergence criterion

Details

If the constraint is "indscale", INDSCALE is performed with configuration weight matrices restricted to be diagonal. IDIOSCALE can be computed using the "idioscale" argument. The weight matrices are then unconstrained. Additional weight restrictions can be imposed with "identity" which restricts the configurations across individuals/replications/ways to be equal

Value

delta	Observed dissimilarities
obsdiss	List of observed dissimilarities, normalized
confdiss	List of configuration dissimilarities
conf	List of matrices of final configurations
gspace	Joint configurations aka group stimulus space
cweights	Configuration weights
stress.m	stress value for metric MDS
stress.nm	stress value for non-metric MDS (if computed)
stress.co	Constrained stress value

spp	Stress per point
sps	Stress per subject (matrix)
ndim	Number of dimensions
model	Type of smacof model
niter	Number of iterations
nobj	Number of objects

Author(s)

Jan de Leeuw and Patrick Mair

References

de Leeuw, J., & Mair, P. (2009). Multidimensional scaling using majorization: The R package smacof. *Journal of Statistical Software*, 31(3), 1-30, <http://www.jstatsoft.org/v31/i03/>

See Also

[smacofConstraint](#), [smacofSym](#), [smacofRect](#), [smacofSphere.primal](#), [smacofSphere.dual](#)

Examples

```
data(perception)

res.id <- smacofIndDiff(perception, constraint = "identity") ## identity restricted weights
summary(res.id)
res.id$cweights
plot(res.id)
plot(res.id, type = "p", pch = 25, col = 4, label.conf = list(label = TRUE, pos = 3, col = 4))

res.diag <- smacofIndDiff(perception, constraint = "indscal") ## diagonally restricted weights
res.diag$cweights
plot(res.diag)
plot(res.diag, type = "p", pch = 25, col = 4, label.conf = list(label = TRUE, pos = 3, col = 4))

res.idio <- smacofIndDiff(perception, constraint = "idioscal") ## IDIOSCAL
Wk <- res.idio$cweights
G <- res.idio$gspace
G
G

data(helm)
res.helm <- smacofIndDiff(helm, constraint = "indscal")
plot(res.helm, plot.type = "confplot")
barplot(sort(res.helm$sps, decreasing = TRUE), main = "Stress per Subject", cex.names = 0.8)
plot(res.helm, plot.type = "bubbleplot")
plot(res.helm, plot.type = "stressplot")
plot(res.helm, plot.type = "Shepard")
plot(res.helm, plot.type = "resplot")
```

 smacofRect

Rectangular smacof

Description

Variant of smacof for rectangular matrices (typically ratings, preferences) which is also known as metric unfolding.

Usage

```
smacofRect(delta, ndim = 2, weightmat = NULL, init = NULL, verbose = FALSE,
            itmax = 1000, reg = 1e-6, eps = 1e-6)
```

Arguments

delta	Data frame or matrix of preferences, ratings, dissimilarities.
ndim	Number of dimensions
weightmat	Optional matrix with dissimilarity weights
init	Matrix with starting values for configurations (optional)
verbose	If TRUE, intermediate stress is printed out
itmax	Maximum number of iterations
reg	Regularization factor, prevents distances from being 0
eps	Convergence criterion

Details

Creates an object of class smacofR.

Value

obsdiss	Observed dissimilarities, corresponds to delta
confdiss	Configuration dissimilarities
conf.row	Matrix of final row configurations
conf.col	Matrix of final column configurations
stress	Final stress value
spp.row	Stress per point, rows
spp.col	Stress per point, columns
ndim	Number of dimensions
model	Type of smacof model
niter	Number of iterations
nind	Number of individuals (rows)
nobj	Number of objects (columns)

Author(s)

Jan de Leeuw and Patrick Mair

References

de Leeuw, J. & Mair, P. (2009). Multidimensional scaling using majorization: The R package smacof. *Journal of Statistical Software*, 31(3), 1-30, <http://www.jstatsoft.org/v31/i03/>

See Also

[smacofConstraint](#), [smacofSym](#), [smacofIndDiff](#), [smacofSphere.primal](#), [smacofSphere.dual](#), [plot.smacof](#)

Examples

```
data(breakfast)
res <- smacofRect(breakfast)
res
summary(res)

## various configuration plots
plot(res)
plot(res, type = "p", pch = 25)
plot(res, type = "p", pch = 25, col.columns = 3, label.conf.columns = list(label = TRUE, pos = 3, col = 3), col.rows = 3)

plot(res, joint = TRUE)
plot(res, joint = TRUE, type = "p", pch = 25, col.columns = 4, label.conf.columns = list(label = TRUE, pos = 3, col = 3), col.rows = 3)
```

smacofSphere.dual *Spherical SMACOF*

Description

Dual and primal approach for spherical SMACOF.

Usage

```
smacofSphere.dual(delta, penalty = 100, ndim = 2, weightmat = NULL, init = NULL,
metric = TRUE, ties = "primary", verbose = FALSE, relax = FALSE, modulus = 1, itmax = 1000, eps = 1e-6)
```

```
smacofSphere.primal(delta, ndim = 2, weightmat = NULL, init = NULL,
metric = TRUE, ties = "primary", verbose = FALSE, modulus = 1, itmax = 1000, eps = 1e-6)
```

Arguments

delta	Either a symmetric dissimilarity matrix or an object of class <code>dist</code>
penalty	Penalty parameter for dual algorithm (larger 0)
ndim	Number of dimensions
weightmat	Optional matrix with dissimilarity weights
init	Matrix with starting values for configurations (optional)
metric	If FALSE non-metric MDS is performed
ties	Tie specification for non-metric MDS only
verbose	If TRUE, intermediate stress is printed out
relax	If TRUE, block relaxation is used for majorization
modulus	Number of smacof iterations per monotone regression call
itmax	Maximum number of iterations
eps	Convergence criterion

Value

delta	Observed dissimilarities
obsdiss	Observed dissimilarities, normalized
obsdiss1	Dual SMACOF: Observed dissimilarities
obsdiss2	Dual SMACOF: Restriction matrix
confdiss	Configuration dissimilarities
conf	Matrix of final configurations
spp	Stress per point
stress.m	stress value for metric MDS
stress.nm	stress value for non-metric MDS (if computed)
ndim	Number of dimensions
dummyvec	Dummy vector of restriction matrix
model	Type of smacof model
niter	Number of iterations
nobj	Number of objects

Author(s)

Jan de Leeuw and Patrick Mair

References

de Leeuw, J. & Mair, P. (2008). Multidimensional scaling using majorization: The R package smacof.

See Also

[smacofRect](#), [smacofIndDiff](#), [smacofSym](#), [smacofConstraint](#)

Examples

```
## spherical SMACOF solution for trading data
data(trading)
res <- smacofSphere.dual(trading)
res
summary(res)
```

smacofSym	<i>Symmetric smacof</i>
-----------	-------------------------

Description

Multidimensional scaling (stress minimization: SMACOF) on symmetric dissimilarity matrix.

Usage

```
smacofSym(delta, ndim = 2, weightmat = NULL, init = NULL, metric = TRUE, ties = "primary", verbose = FALSE)
```

Arguments

delta	Either a symmetric dissimilarity matrix or an object of class "dist"
ndim	Number of dimensions
weightmat	Optional matrix with dissimilarity weights
init	Matrix with starting values for configurations (optional)
metric	If FALSE non-metric MDS is performed
ties	Tie specification for non-metric MDS only: "primary", "secondary", or "tertiary"
verbose	If TRUE, intermediate stress is printed out
relax	If TRUE, block relaxation is used for majorization
modulus	Number of smacof iterations per monotone regression call
itmax	Maximum number of iterations
eps	Convergence criterion

Details

This is the simplest MDS-SMACOF version of the package. It solves the stress target function for symmetric dissimilarity means of the majorization approach (SMACOF). The main output are the coordinates in the low-dimensional space (configurations; `conf`). The function also returns the point stress, i.e. the larger the contribution of a point to the total stress, the worse the fit (see also [plot.smacof](#)).

Value

delta	Observed dissimilarities
obsdiss	Observed dissimilarities, normalized
confdiss	Configuration dissimilarities
conf	Matrix of final configurations
stress.m	Stress value for metric MDS
stress.nm	Stress value for non-metric MDS (if computed)
spp	Stress per point
ndim	Number of dimensions
model	Type of smacof model
niter	Number of iterations
nobj	Number of objects

Author(s)

Jan de Leeuw and Patrick Mair

References

de Leeuw, J. & Mair, P. (2009). Multidimensional scaling using majorization: The R package smacof. *Journal of Statistical Software*, 31(3), 1-30, <http://www.jstatsoft.org/v31/i03/>

See Also

[smacofConstraint](#), [smacofRect](#), [smacofIndDiff](#), [smacofSphere.primal](#), [smacofSphere.dual](#), [plot.smacof](#)

Examples

```
## simple SMACOF solution for kinship data
data(kinshipdelta)
res <- smacofSym(kinshipdelta)
res
summary(res)
plot(res)
plot(res, type = "p", label.conf = list(TRUE, 3, "darkgray"), pch = 25, col = "red")

## 3D nonmetric SMACOF solution for trading data
data(trading)
res <- smacofSym(trading, ndim = 3, metric = FALSE, ties = "secondary")
res
```

 stardist

Distances among stars in zodiac signs

Description

A distance matrix for the 10 brightest stars in each of the 12 zodiac signs was computed. Astronomers measure the projected positions of objects on the celestial sphere in two angles, i.e. right ascension α and declination δ . For every zodiac sign, the projected distances on the sky between individual stars S_i and S_j have been calculated in decimal degrees by means of the Pythagorean theorem

$$d_{i,j} = \sqrt{(\alpha_i - \alpha_j)^2 + (\delta_i - \delta_j)^2}$$

assuming planar geometry. Since the zodiac signs are relatively small compared to the whole celestial sphere and the computation is only done for illustrative purposes, such a simplified assumption is appropriate.

Usage

```
data(stardist)
```

Format

A dist object containing the star distances.

Note

Thanks to Paul Eigenthaler, Department of Astronomy, University of Vienna for calculating the distances.

Examples

```
data(stardist)
```

 summary.smacofB

S3 methods for smacof

Description

Print and summary methods for objects of class smacofB, smacofR (rectangular), and smacofID (individual differences).

Usage

```
## S3 method for class 'smacofB'
summary(object, ...)
## S3 method for class 'smacofB'
print(x, ...)
## S3 method for class 'smacofR'
summary(object, ...)
## S3 method for class 'smacofR'
print(x, ...)
## S3 method for class 'smacofID'
summary(object, ...)
## S3 method for class 'smacofID'
print(x, ...)
```

Arguments

object	Object of class smacofB, smacofR, smacofID
x	Object of class smacofB, smacofR, smacofID
...	Ignored

Examples

```
data(kinshipdelta)
res <- smacofSym(kinshipdelta)
res
summary(res)
```

trading

Trading data

Description

Data from the New Geographical Digest (1986), analysed in Cox and Cox (2001), on which countries traded with other countries. For 20 countries the main trading partners are dichotomously scored (1 = trade performed, 0 = trade not performed). Based on this dichotomous matrix the dissimilarities are computed using the Jaccard coefficient.

Usage

```
data(trading)
```

Format

Object of class "dist" with dissimilarities of the following countries:

Arge: Argentina

Aust: Australia

Braz: Brazil

Cana: Canada

Chin: China

Czec: Czechoslovakia

Egyp: Egypt

E.Ge: East Germany

Fran: France

Hung: Hungary

Indi: India

Ital: Italy

Japa: Japan

N.Ze: New Zealand

Pola: Poland

Swed: Sweden

USA

USSR: Soviet Union

U.K.: United Kingdom

W.Ge: West Germany

References

Cox, T.F., Cox, M.A.A. (1991). Multidimensional scaling on a sphere. *Communications in Statistics: Theory and Methods*, 20, 2943-2953.

Examples

```
data(trading)
```

winedat

Wine tasting

Description

This dataset collects dissimilarity matrices of 10 raters of 6 different wines.

Usage

```
data(winedat)
```

Format

A list of dissimilarity matrices reflecting the rating of 10 judges on 6 different wines (Ziniel Chardonnay, Markowitsch Chardonnay, Krems Chardonnay, Castel Nova Chardonnay, Ritinitis Noble Retsina, RetsinaCriteria). The attributes color, smell, taste, fun, and overall impression were rated on a scale from 1 (very good) to 5. Based on these ratings the distances were computed.

Examples

```
data(winedat)
```

wish_ger

Wish dataset

Description

Similarity ratings for 12 countries. There were no instructions concerning the characteristics on which these similarity judgements were to be made, this was information to discover rather than to impose.

Usage

```
data(wish)
```

Format

Object of class `dist`

Details

Note that for `wish_ger` the country labels are given in German. For `smacof`, the data must be converted into a dissimilarity matrix (see examples).

References

- Borg, I., Groenen, P. J. F., & Mair, P. (2010). *Multidimensionale Skalierung*. Muenchen: Hampp Verlag.
- Borg, I., Groenen, P. J. F., & Mair, P. (2012). *Multidimensional Scaling*. New York: Springer, forthcoming.
- Wish, M. (1971). Individual differences in perceptions and preferences among nations. In C. W. King and D. Tigert (Eds.), *Attitude research reaches new heights*, pp. 312-328. Chicago: American Marketing Association.

Examples

```
data(wish)
sim2diss(wish)
```

Index

*Topic **datasets**

- bread, [3](#)
- breakfast, [4](#)
- csrranking, [5](#)
- ekman, [5](#)
- EW_ger, [6](#)
- helm, [7](#)
- kinshipdelta, [10](#)
- partypref, [10](#)
- perception, [11](#)
- rectangles, [17](#)
- stardist, [29](#)
- trading, [30](#)
- winedat, [32](#)
- wish_ger, [32](#)

*Topic **hplot**

- jackknife, [8](#)
- plot.smacof, [13](#)
- plot3d.smacof, [15](#)

*Topic **methods**

- residuals.smacof, [18](#)
- summary.smacofB, [29](#)

*Topic **models**

- permtest, [12](#)
- sim2diss, [18](#)
- smacofConstraint, [19](#)
- smacofIndDiff, [21](#)
- smacofRect, [24](#)
- smacofSphere.dual, [25](#)
- smacofSym, [27](#)

*Topic **package**

- smacof-package, [2](#)

bread, [3](#)

breakfast, [4](#)

csrranking, [5](#)

ekman, [5](#)

EW_eng (EW_ger), [6](#)

EW_ger, [6](#)

helm, [7](#)

jackknife, [8](#)

jackknife.smacofB, [13](#)

kinshipdelta, [10](#)

kinshipscales (kinshipdelta), [10](#)

partypref, [10](#)

perception, [11](#)

permtest, [12](#)

plot, [8](#), [12](#), [14](#), [16](#)

plot.smacof, [9](#), [13](#), [13](#), [16](#), [25](#), [27](#), [28](#)

plot.smacofID (plot.smacof), [13](#)

plot.smacofJK (jackknife), [8](#)

plot.smacofPerm (permtest), [12](#)

plot.smacofR (plot.smacof), [13](#)

plot3d.smacof, [15](#), [15](#)

plot3d.smacofID (plot3d.smacof), [15](#)

plot3d.smacofR (plot3d.smacof), [15](#)

plot3dstatic (plot3d.smacof), [15](#)

print.smacofB (summary.smacofB), [29](#)

print.smacofID (summary.smacofB), [29](#)

print.smacofJK (jackknife), [8](#)

print.smacofPerm (permtest), [12](#)

print.smacofR (summary.smacofB), [29](#)

rainbow_hcl, [8](#)

rect_constr (rectangles), [17](#)

rectangles, [17](#)

residuals.smacof, [18](#)

residuals.smacofID (residuals.smacof),
[18](#)

residuals.smacofR (residuals.smacof), [18](#)

sim2diss, [18](#)

smacof, [3](#)

smacof (smacof-package), [2](#)

smacof-package, [2](#)

smacofConstraint, 9, 19, 23, 25, 27, 28
smacofIndDiff, 3, 21, 21, 25, 27, 28
smacofRect, 3, 21, 23, 24, 27, 28
smacofSphere.dual, 3, 21, 23, 25, 25, 28
smacofSphere.primal, 3, 21, 23, 25, 28
smacofSphere.primal
 (smacofSphere.dual), 25
smacofSym, 3, 9, 13, 21, 23, 25, 27, 27
stardist, 29
summary.smacofB, 29
summary.smacofID (summary.smacofB), 29
summary.smacofR (summary.smacofB), 29

trading, 30

winedat, 32
wish (wish_ger), 32
wish_ger, 32